

ERGO Tool Balancers

Keep workers, tools, and equipment safe

Introduction

Operate safely in the workplace with ERGO. Our ranges help protect against injury, and reduce the risk of damage to equipment.

Air hose balancers used to suspend air hoses workshops and industrial settings, allowing for safe and efficient use of pneumatic tools.

Experience the ERGO difference

- Drum design minimizes hose overlapping for smooth extending/recoiling
- Durable hose material maximizes performance
- Quality spring technology, field-proven on our cable tool balancers
- Rugged, lightweight aluminum case







Reduce Fatigue



Clean Workstation

ERGO 1 BD Series

The ERGO 1 is suitable for small drills and equipment weighing up to 5lbs. The choice for a range of simple applications in a variety of industrial locations.

Reliable & Economical Series 'BD'


SERIES 'BD' TOOL BALANCERS are the economical choice for balancing tools weighing up to 5 lbs (2.3kg). Molded ABS housing has a smooth exterior with rounded edges designed for maximum ergonomic appeal. Series "BD" balancers are the most modern, easiest to adjust, and reliable. Each balancer incorporates all of the important functions expected of a world class product.



Seven ways better

- Hand-windable spring tension adjustment knob is flush with the housing
- 2. Push-button tension release simplifies decrease of spring tension
- 3. Rugged steel upper swivel hook with secondary safety cable provision
- 4. Over-sized cable opening with direct in-line pull to reduce cable wear
- 5. 270 lb (121.5kg) test 0.047" (1.2mm) dia. 7 x 7 strand galvanized steel aircraft cable nylon covered to 0.063" (1.6mm) O.D
- 6. Adjustable cable stop and lower safety hook
- 7. Matte black finish to minimize reflected light and reduce eye strain

Series 'BD' Dimensions



Selection Chart

Min - Max Load lbs. (kg.)	Cable Length* ft. (m.)	Reel Weight Ibs. (kg.)	Model Number	
0.5 - 1.5 (0.2 -0.7)	6 (1.8)	1.3 (0.6)	BD-01	
1.5 - 3.0 (0.5 - 1.4)	6 (1.8)	1.3 (0.6)	BD-03	
3.0 - 5.0 (1.4 - 2.3)	6 (1.8)	1.5 (0.7)	BD-05	

^{*}Cable lengths listed are for "active" or "workable" cable. Includes cable stop and safety hook.

ERGO 2 BG Series


Suitable for tools up to 27lbs in weight, it's our heavy duty solution for larger applications that need extra strength.

Heavy Duty Series 'BG'

SERIES 'BG' reels feature rugged steel construction with black polyester baked finish, reinforced hanging bracket with forged clevis for ceiling mounting and extra holes for safety chain attachment. Spring is permanently lubricated and provides constant tension, adjustable for balancing tool in normal working zone. Cable is 920 lb. (414kg) test 0.09" (2.3mm) dia. 7 x 7 strand galvanized steel aircraft cable nylon covered to 0.12" (3.0mm) O.D. Includes safety tool clip and adjustable cable stop.

LOCKING MODELS include all features listed above plus a positive ratchet lock mechanism to allow locking of the cable at a specific height. A slight pull on the cable releases the lock which functions like a window shade. Lock feature may be disengaged externally when constant tension is required.

Series 'BG' Dimensions





Min - Max Load Ibs. (kg.)	Cable Length* ft. (m.)	Ratchet Lock	Reel Weight lbs. (kg.)	Model Number
Balancers (CONSTANT	PULL REELS). May be a	djusted to balance throug	gh 6-18 in.(152-457mm) ra	inge.
3 - 7 (1.4 - 3.2)	8 (2.4)	No	6 (2.7)	BG-03
5 - 10 (2.3 - 4.5)	8 (2.4)	No	6 (2.7)	BG-07
8 - 12 (3.6 - 5.4)	8 (2.4)	No	7 (3.2)	BG-10
10 - 15 (4.5 - 6.8)	8 (2.4)	No	8 (3.6)	BG-15
16 - 23 (7.2 - 10.4)	8 (2.4)	No	8 (3.6)	BG-20
16 - 23 (7.2 - 10.4)	8 (2.4)	No	8 (3.6)	BG-20SH**
22 - 27 (9.9 - 12.2)	8 (2.4)	No	8 (3.6)	BG-25

^{**}This note applies to the key under the tables on the next page about cable lengths and Shock Stop.

ERGO 1 & 2 Accessories

Our range of accessories work seamlessly with our ERGO 1&2 models (BH and BG Series).

#STC-01 Safety Clip

Bright zinc plated steel safety latch for tool attachment and other uses. Measures 2.375"(60mm) long. One included with each BG reel. Rated capacity-70 lbs.

Clevis Hangers

Galvanized forged steel hangers for mounting balancers, torque reels, etc. Measure 0.50" (13mm) between jaws. One #CVF-01 straight clevis included with each "BG" & "TQ" reel. #CVF-11 swivel clevis is optional, extra pins included. Rated capacity-500 lbs.

#CVF-01 **CLEVIS**





Retractors (Ratchet Lock) Retract tool upward when manually released

3 - 7 (1.4 - 3.2)	8 (2.4)	Yes	6 (2.7)	BG-03-L
5 - 10 (2.3 - 4.5)	8 (2.4)	Yes	6 (2.7)	BG-07-L
8 - 12 (3.6 - 5.4)	8 (2.4)	Yes	7 (3.2)	BG-10-L
10 - 15 (4.5 - 6.8)	8 (2.4)	Yes	8 (3.6)	BG-15-L
16 - 23 (7.2 - 10.4)	8 (2.4)	Yes	8 (3.6)	BG-20-L
16 - 23 (7.2 - 10.4)	8 (2.4)	Yes	8 (3.6)	BG-20-LSH**
22 - 27 (9.9 - 12.2)	8 (2.4)	Yes	8 (3.6)	BG-25

Torque Reels (Ratchet Lock and Longer Cable)

3 - 7 (1.4 - 3.2)	15.0 (4.5)	Yes	8 (3.6)	TQ1507
5 - 10 (2.3 - 4.5)	15.0 (4.5)	Yes	10 (4.5)	TQ1510
8 - 12 (4.5 - 6.8)	15.0 (4.5)	Yes	12 (5.4)	TQ1515

^{*}Cable lengths listed are "active" or "working" cable.

Adjustable Cable Saddle


Hangs from balancer cable above tool to provide strain relief for electrical cable or air hose. Available in three sizes. Includes safety clip.



Cable Diameter in. (mm)	Model Number
0.3 - 0.59 (7 - 14)	CS-F1
0.6 - 0.94 (15 - 23)	CS-F2
0.95 - 1.25 (24 - 31)	CS-F3

Overhang Cable

Nylon covered steel cable with safety clip. Brings tool closer to work area without unwinding cable from reel or mounting reel at a lower height.



	Length ft. (m)	Model Number
— Length	3 (0.9)	OC-03
5	5 (1.5)	OC-05
U	10 (3.0)	OC-10
	15 (4.6)	OC-15

"Shock Stop" Shock Absorber

Minimize cable damage often caused by overtensioning tool balancers. "Shock Stop" kit is easily installed. Can be used on any Series BD or BG balancer. Kit includes spring, cable stops, all hardware.



Model Number
BD-SH
BG-SH

NEW!

Now available for BD Series


^{**}Includes BG-SH "Shock Stop". See Below.

All models are clevis mount. For rigid mount add

[&]quot;-R" to model number.

Safety Cable/Chain

We strongly advise the use of a secondary safety cable alongside the standard installations of our ERGO balancers. These help prevent accidental fall. Safety cable can be attached to the additional holes provided across the ranges. Refer to the table below to choose the correct cable for use with each model of balancer.



Length ft. (m)	Model No
1.0 (0.3)	SC-BD1*
1.0 (0.3)	SC-BG1**
2.0 (0.6)	SC-BG2**
3.0 (0.9)	SC-BG3**

^{*}Nylon covered steel cable.

ERGO 3 BH Series

The largest and strongest of our ranges, the ERGO 3 is suitable for larger balancer applications, for tools and equipment up to 308 lbs.

Tapered Drum Tool Balancers (Accessories)

For tools from 1.1 to 308 pounds


Heavy-duty construction. Tapered drum compensates for changing spring rate. Direct spring powered, no motors or expensive gear trains to break or wear out.

Series "BH" Tapered Drum Tool Balancers keep tools within reach and reduce damage to tools by suspending them out of the way above the work surface. Risk of repetitive motion injury is reduced because only a light, downward force is required to place the tool in proper operating position. As the tool is lowered, and the spring is wound more tightly, the effective drum diameter increases to compensate for the increased force. Thus, when properly adjusted, the tapered drum keeps the tool at the positioned height.

Features include:

- Rugged die cast aluminum housing
- Both top and bottom hooks have spring-loaded safety latches
- Heavy duty steel wire rope
- · Automatic safety catch prevents free-spooling if springs fail (not available on BH-02/BH-05)
- Easy adjustment with everyday tools

^{**}Steel link chain.



Selection Chart							
For Tool Cable Shipping Model Weighing* Cable Weight Number							
1.1 - 4.4 lbs.	3.3 ft.	2.2 lbs.	BH-02				
2.2 - 6.6 lbs.	4.3 ft.	2.8 lbs.	BH-03				
5.5 - 11 lbs.	4.3 ft.	3.3 lbs.	BH-05				
9 - 20 lbs.	3.9 ft.	13.4 lbs.	BH-09				
20 - 33 lbs.	3.9 ft.	13.4 lbs.	BH-15				
33 - 48 lbs.	4.5 ft.	22.6 lbs.	BH-22				
48 - 66 lbs.	4.5 ft.	22.6 lbs.	BH-30				
66 - 88 lbs.	4.5 ft.	27.0 lbs.	BH-40				
88 - 110 lbs.	4.5 ft.	27.0 lbs.	BH-50				
110 - 132 lbs.	4.5 ft.	31.4 lbs.	BH-60				
132 - 154 lbs.	4.5 ft.	31.4 lbs.	BH-70				
154 - 187 lbs.	4.5 ft.	58.4 lbs.	BH-85				
187 - 220 lbs.	4.5 ft.	56.0 lbs.	BH-100				
220 - 264 lbs.	4.5 ft.	60.0 lbs.	BH-120				
264 - 308 lbs.	4.5 ft.	61.0 lbs.	BH-140				

Dimensional Chart							
Model	A	В	C**	D	E		
BH-02	5.43 in.	7.28 in.	9.06 in. min.	1.97 in.	0.67 in.		
BH-03/BH-05	5.83 in.	7.68 in.	10.71 in. min.	2.72 in.	1.26 in.		
BH-09/BH-15	7.09 in.	9.53 in.	13.62 in. min.	5.35 in.	2.83 in.		
BH-22/BH-30	8.58 in.	8.70 in.	22.32 in. min.	6.22 in.	3.15 in.		
BH-40/BH-70	8.66 in.	12.32 in.	22.32 in. min.	7.40 in.	4.13 in.		
BH-85	8.66 in.	12.32 in.	22.32 in. min.	7.83 in.	4.57 in.		
BH-100/BH-140	10.89 in.	13.90 in.	24.84 in. min.	10.22 in.	3.63 in.		


^{**} Minimum height fully retracted, inside of hook to inside of hook.

Safety Chain (recommended)					
Description	Model Number				
2.0 ft. Steel Link Chain w/ Clevises	1.5 lbs.	SC-BH2			
3.0 ft. Steel Link Chain w/ Clevises	2.0 lbs.	SC-BH3			

^{*} Tool weight includes hose or cord and other attachments which must be supported by balancer.

Accessories For BH Tool Balancers

Series BH Tool Balancer Accessories						
Balancer Model No.	Capacity		Safety Chain	Overhang Cable (4)	Tool Trolley	
	Lbs.	(Kg)				
BH-02 (1)	1.1 - 4.4	(0.5 - 2.0)	NONE	OC-XX	WS30-BTL (6)	
BH-03 (1)	2.2 - 6.6	(1.0 - 3.0)	SC-BG3	OC-XX	WS30-BTL (6)	
BH-05 (1)	5.5 - 11	(2.5 - 5.0)	SC-BG3	OC-XX	WS30-BTL (6)	
BH-09 (1)	9 - 20	(4.1 - 9.1)	SC-BG3	OC-XX (5)	WS50-BTL	
BH-15 (2)	20 - 33	(9.1 - 15)	SC-BG3	OC-XX (5)	WS50-BTL	
BH-22 (2)	33 - 48	(15 - 21.8)	SC-BG3	OC5MB-XX	WS50-BTL	
BH-30 (2)	48 - 66	(21.8 - 30.0)	SC-BG3	OC5MB-XX	WS60-BT	
BH-40 (2)	66 - 88	(30.0 - 40.0)	SC-BH3	OC5MB-XX	WS60-BT	
BH-50 (2)	88 - 110	(40.0 - 50.0)	SC-BH3	OC5MB-XX	WS60-BT	
BH-60 (2)	110 -132	(50.0 - 60.0)	SC-BH3	OC5MB-XX	WS60-BT	
BH-70 (2)	132 -154	(60.0 - 70.0)	SC-BH3	OC5MB-XX	WS60-BT	
BH-85 (2)	154 -187	(70.0 - 85.0)	SC-BH3	OC8MB-XX	WS60-BT	
BH-100 (3)	187 - 220	(85.0 - 100.0)	SC-BH3	OC8MB-XX	W6S-BT	
BH-120 (3)	220 - 264	(100.0 -120.0)	SC-BH3	OC8MB-XX	W6S-BT	
BH-140 (3)	264 - 308	(120.0 - 140.0)	SC-BH3	OC8MB-XX	W6S-BT	



- Balancer hook will fit WS30-BTL or WS50-BTL Tool Trolley
- 2. Balancer hook will fit either WS50-BTL, WS60-BT or W6S-BT Tool Trolley
- 3. Balancer hook will fit only W6S-BT Tool Trolley
- 4. "XX" = Length req'd. When ordering indicate, -03 = 3 ft., -05 = 5 ft. or -10 = 10 ft
- 5. Use with BH-09 or BH-15 requires one additional STC-01 Safety Clip
- 6. WS50-BTL may also be used with BH-02, BH-03 and BH-05

Repair Parts for BH Tool Balancers

BH-09 - 70 Balancers				
Model Number	Description			
BH09-SPG	SPRING FOR BH-09			
BH15-SPG	SPRING FOR BH-15			
BH22-SPG	SPRING FOR BH-22			
BH30-SPG	SPRING FOR BH-30			
BH40-SPG	SPRING FOR BH-40			
BH50-SPG	SPRING FOR BH-50			
BH60-SPG	SPRING FOR BH-60			
BH70-SPG	SPRING FOR BH-70			
BH915-CBL	CABLE FOR BH-09 & BH-15			
BH2270-CBL	CABLE FOR BH-22 THRU BH-70			
BH915-DRM	DRUM FOR BH-09 & BH-15			
BH2270-DRM	DRUM FOR BH-22THRU BH-70			

BH-02 - 05 Balancers				
Model Number	Description			
BH02-SPG	SPRING W/DRUM FOR BH-02			
BH03-SPG	SPRING W/DRUM FOR BH-03			
BH05-SPG	SPRING W/DRUM FOR BH-05			
BH02-CBL	CABLE FOR BH-02			
BH03-CBL	CABLE FOR BH-03			
BH05-CBL	CABLE FOR BH-05			

BH85 - BH140 Balancers			
Model Number	Description		
BH85-SPG	SPRING FOR BH-85		
BH100-SPG	SPRING FOR BH-100		
BH120-SPG	SPRING FOR BH-120		
BH140-SPG	SPRING FOR BH-140		
BH85140-DRM	DRUM W/CABLE FOR BH-85 THRU BH-140		

ERGO 4 BT Series

Maximize work desk space and keep air tools safely contained with the ERGO 4 BT Series. Our air hose balancer is suitable for air tools up to 11 lbs in weight.

Hang your air powered tools directly from the hose with the ERGO 4 hose balancer. It suspends the tool and supplies the air, reducing operator fatigue, improving workplace safety, and reducing tool breakage.


The balancer suspends the tool directly over the workstation. It easily adjusts to make the tool seem near-weightless when pulled down to the task at hand, then lifts it and the hose up out of way for stand-by or storage. At the desired height, the balanced tool won't drift up or down.

Benefits

- Reduce injury: Lessen expensive repetitive motion injuries from heavy tools. See "Selection Chart" for more
- Reduce worker fatigue: Adjusting the tool to virtually weightless supports worker precision and efficiency
- Clean up workstation: Lifting the tool out of the way provides easy access and keeps the air line from being a trip hazard
- Save money on tools: Tethering to the workstation prevents tool from getting dropped, broken, lost, or stolen, reducing replacements
- Reduce air line replacements: Extend air line life by eliminating damage from being dragged around, tripped on, or driven over



Dimensional Drawings



Selection Chart

Min - Max Load		Cable Length		Balancer Weight		Model
Lbs	(KG)	FT	М	Lbs	(KG)	Number
0.9-1.75	(0.4-0.8)	4.4	(1350)	2.75	(1.25)	BT-9200
1.6-3.3	(0.75-1.5)	4.4	(1350)	2.9	(1.3)	BT-9201
2.6- 5.5	(1.2-2.5)	4.4	(1350)	3	(1.35)	BT-9202
6.6-11	(3-5)	2.95	(900)	3.5	(1.6)	BT-9203

Improve workstation safety

Our Tool Balancers help improve workstation safety and promote efficient use, keeping work areas tidy and free from cords. They reduce the strain felt by operators when moving pneumatic tools, making them feel weightless.

The complete Ergo line has your tools covered, no matter how heavy

Model	Application
ERGO 1 BD	Small equipment up to 5lbs
ERGO 2 BG	Tools up to 27lbs
ERGO 3 BH	Equipment up to 308lbs
ERGO 4 BT	Air tools up to 11lbs



A key part of the ToolAssistPro line

According to the U.S. Bureau of Labor Statistics, 33% of workplace injuries result directly from poor ergonomics. Workplace safety products better fit both tasks and workers, increasing your profitability through productivity and efficiency.

Complete line of material handling and workplace safety solutions

Lower your total ownership cost through ergonomic workstation design, proper equipment, and preventing tools from getting broken or lost. Our solutions include everything you need:









Torque arms

Carts & Workstations

Cranes & Festoons

Cable Reels

Effective material handling and ergonomics pay dividends!

Contact your Gleason Reel sales representative today.

