

# Twist-Lock<sup>®</sup> Edg<sup>@</sup> Series

Twist-Lock® Receptacles with Screwless Terminations



00036



# Twist-Lock<sup>®</sup> Receptacles with Screwless Terminations

Hubbell's innovative Twist-Lock<sup>®</sup> Edge Series receptacles with screwless terminations are the fastest devices to terminate on the market.

# Get the Twist-Lock® Edge

#### **Edge on Speed**

Decrease your installation time by over 80%, technicians can complete the installation completely by hand without a torque driver or wrench

#### **Edge on Safety**

Consistent reliable connection No exposed metal on the receptacle

### **Edge on Durability**

Wires stay tight for the long term, regardless of vibration, temperature cycling or strand relaxation

C

#### **Edge on Reliability**

Same great quality you have come to expect from Hubbell

# Twist-Lock<sup>®</sup> Receptacles with Screwless Terminations


# Features

- Strong spring continues to apply pressure as strands relax
- No exposed metal on receptacles, allowing more devices to be installed closer together
- No torque screwdrivers required for wiring

# Labor Savings

Easy as: 1, 2, 3.







# Twist-Lock® Single Receptacles

Description	Amps	125 Volts	250 Volts
Spring termination locking receptacles	20A	HBL2310ST	HBL2320ST
	30A	HBL2610ST	HBL2620ST

Note: With this new termination method, the CE Code Part I requirements for the use of a torque driver to secure the terminations are no longer applicable.





Note: Terminations can be unwired by simply moving the plunger upwards to the open position.






# *Twist-Lock<sup>®</sup> Edge Series*


# **Twist-Lock® Receptacles with Screwless Terminations**



#### Product Dimensions Inches (mm)

Catalog Number	Amps	Α	В	С	D	E	F	G	Н
HBL2310ST	20A	3.28"	2.38"	1.56"	.24"	1.17"	1.45"	2.77"	1.70"
HBL2320ST		(83.3)	(60.3)	(39.6)	(6.0)	(29.8)	(36.8)	(70.4)	(43.2)
HBL2610ST	30A	3.28"	2.38"	1.56"	.24"	1.26"	1.53"	2.77"	1.70"
HBL2620ST		(83.3)	(60.3)	(39.6)	(6.1)	(32.0)	(39.0)	(70.4)	(43.2)





#### Certifications

cULus Listed by UL to UL498 and CSA C22.2 No. 42. Indoor Dry environment unless protected by additional means.

# Additional Literature

Hubbell offers an extensive literature library for product support. Downloadable PDFs are available online at *www.hubbell-wiring.com*.





www.hubbell.ca

HUBBELL

 HUBBELL CANADA
 • 870 Brock Road South
 • Pickering, ON
 L1W
 1Z8

 Tel. (905)
 839-1138
 • Fax
 (905)
 839-9108
 Printed in Canada. Specifications subject to change without notice.