



## 60/40 Device Plate Combination

- Allows for up to twelve data/AV jacks plus a 20A duplex receptacle
- Two plates which can be wired independently

## 50/50 Device Plate Combination

- Allows for up to eight Hubbell data jacks plus two 20A duplex receptacles
- Two plates which can be wired independently

### Left 60% Sub-Plates

Description	Catalog No.
(1) Style Line® decorator, (2) Extron® MAAP openings <sup>1</sup>	<b>S1R6SPV</b>
(2) Style Line decorator openings <sup>1</sup>	<b>S1R6SPW</b>
(1) Style Line decorator, (2) Extron AAP openings <sup>1</sup>	<b>S1R6SPX</b>
(1) Style Line decorator, (2) 1.5 unit Hubbell iSTATION openings <sup>1,2</sup>	<b>S1R6SPY</b>
(6) Extron MAAP openings <sup>1</sup>	<b>S1R6SPT</b>
(2) Extron MAAP, (2) Extron AAP openings <sup>1</sup>	<b>S1R6SPU</b>

### Right 40% Sub-Plates

Description	Catalog No.
(2) 20A pre-wired receptacles; 16" lead; one circuit (Supplied with isolated ground sticker)	<b>S1R6SPZ</b>
(2) 20A pre-wired receptacles; 25 foot lead; one circuit (Supplied with isolated ground sticker)	<b>S1R6SPZ25</b>
(2) 20A pre-wired receptacles; 16" lead; one circuit (supplied with isolated ground sticker); marked with "Controlled"	<b>S1R6SPZC</b>

### 6" Accessories

Description	Catalog No.															
Pre-pour tube, including hardware	<b>S1R6PPT*</b>															
Abandonment plate, black finish	<b>S1R6ADMTBK</b>															
Low voltage replacement divider	<b>S1R6DIV</b>															
Power junction box, 27.0 cubic inches; (1) 3/4" and (1) 1" EMT connector	<b>S1FRPTJB</b>															
4n" power junction box with cover and fittings; (1) 2" and (1) 1 1/4" EMT connector	<b>S1FRPTJB2</b>															
Replacement plugs	<table border="0"> <tr> <td>Aluminum</td> <td><b>S1RPLUG2ALU</b></td> <td><b>S1RPLUG075ALU</b></td> </tr> <tr> <td>Black</td> <td><b>S1RPLUG2BLK</b></td> <td><b>S1RPLUG075BLK</b></td> </tr> <tr> <td>Brass</td> <td><b>S1RPLUG2BRS</b></td> <td><b>S1RPLUG075BRS</b></td> </tr> <tr> <td>Bronze</td> <td><b>S1RPLUG2BRZ</b></td> <td><b>S1RPLUG075BRZ</b></td> </tr> <tr> <td>Nickel</td> <td><b>S1RPLUG2NKL</b></td> <td><b>S1RPLUG075NKL</b></td> </tr> </table>	Aluminum	<b>S1RPLUG2ALU</b>	<b>S1RPLUG075ALU</b>	Black	<b>S1RPLUG2BLK</b>	<b>S1RPLUG075BLK</b>	Brass	<b>S1RPLUG2BRS</b>	<b>S1RPLUG075BRS</b>	Bronze	<b>S1RPLUG2BRZ</b>	<b>S1RPLUG075BRZ</b>	Nickel	<b>S1RPLUG2NKL</b>	<b>S1RPLUG075NKL</b>
Aluminum	<b>S1RPLUG2ALU</b>	<b>S1RPLUG075ALU</b>														
Black	<b>S1RPLUG2BLK</b>	<b>S1RPLUG075BLK</b>														
Brass	<b>S1RPLUG2BRS</b>	<b>S1RPLUG075BRS</b>														
Bronze	<b>S1RPLUG2BRZ</b>	<b>S1RPLUG075BRZ</b>														
Nickel	<b>S1RPLUG2NKL</b>	<b>S1RPLUG075NKL</b>														

\*Note: UL Listed  
<sup>1</sup>Sub-plates may only be used for Data/AV. Do not mix with power devices.  
<sup>2</sup>See section F for Hubbell iSTATION modules.  
 Note: Sub-plates can not be rotated to create additional layouts. When assembled, sub-plates can not overlap. Custom plates available upon request and may be subject to minimum order quantity.  
 Extron is a registered trademark of Extron Electronics. Crestron is a registered trademark of Crestron Electronics, Inc. FSR is a registered trademark of FSR Inc.

### Left 50% Sub-Plates

Description	Catalog No.
(3) Extron® AAP openings	<b>S1R6SPA</b>
(5) Extron MAAP openings	<b>S1R6SPC</b>
(1) Style Line Decorator, (2) Hubbell keystone openings <sup>1</sup>	<b>S1R6SPE</b>
(3) Extron MAAP, (2) Hubbell keystone jack openings	<b>S1R6SPL</b>
Blank cover plate	<b>S1R6SPB</b>
(4) 1 unit Hubbell iSTATION openings <sup>2</sup>	<b>S1R6SPD</b>
(2) 1.5 unit Hubbell iSTATION openings <sup>2</sup>	<b>S1R6SPF</b>
(1) Style Line® decorator opening	<b>S1R6SPM</b>
(1) Decorator opening and (2) Ortronics® TracJack® openings	<b>S1R6SPN</b>
2 Jack openings and 4 Jack KOs, 50% left Side	<b>S1R6SP6DJ</b>

### Right 50% Sub-Plates

Description	Catalog No.
(1) 1.60" opening for 20A and 30A Twist-Lock®	<b>S1R6SPG</b>
(1) Duplex device opening	<b>S1R6SPI</b>
(1) Style Line® decorator device opening	<b>S1R6SPK</b>
(4) 20A pre-wired receptacles; 16" leads; one or two circuits (Supplied with isolated ground sticker)	<b>S1R6SPH</b>
(1) 1.4" opening for simplex or 15A Twist-Lock	<b>S1R6SPJ</b>

### Recessed 6" Covers

6" FRPT cover assembled unit includes solid cast aluminum construction, carpet gasket and mounting hardware.

Description	Catalog No.	Furniture Feed Option
Brushed Aluminum	<b>S1R6CVRALU</b>	<b>S1R6FFCVRALU</b>
Black Powder Coat	<b>S1R6CVRBLK</b>	<b>S1R6FFCVRBLK</b>
Brushed Brass Plated	<b>S1R6CVRBRS</b>	<b>S1R6FFCVRBRS</b>
Antique Bronze Plated	<b>S1R6CVRBRZ</b>	<b>S1R6FFCVRBRZ</b>
Gray Powder Coat	<b>S1R6CVRGRY</b>	<b>S1R6FFCVRGRY</b>
Satin Nickel Plated	<b>S1R6CVRNKL</b>	<b>S1R6FFCVRNKL</b>

Note: Cover Load Rating: 1,000lb with 2x safety factor; load applied through a 3" (76mm) dia. mandrel at center of cover; rated for static loads only



Complies with UL514 A & C