Description Style Line® Decorator/ **GFCI**

(2) Style Line decorator openings for power and/or datacom applications



Description Duplex/Duplex

(2) duplex openings for power and/or datacom applications



S1SPDU

Catalog No. Description **Duplex/Style Line®** Decorator

(1) duplex and (1) Style Line decorator opening for power and/or datacom applications



Hubbell 4 X 4

(4) 20A, 125V receptacles, (4) keystone openings for Hubbell jacks or flush AV connectors; power can be wired as single or two circuit with isolated ground capability



S1SP4X4

Carpet Furniture Feed Cover/Flange* (1) 3/4" and (1) 11/2" NPT access

holes for power and/or datacom applications; universal cover not required; includes carpet flange



Tile Furniture Feed Cover/Flange*

(1) ³/₄" and (1) 1½" NPT access holes for power and/or datacom applications; universal cover not required; includes tile flange



Provided with 30' wire leads

Provided with 15' wire leads S1SP4X415 S1SP4X430 Aluminum Fin. S1SPFFAL S1SPFFBRS Brass Fin. Black S1SPFFBL Gray S1SPFFGY

Brass Fin. Black Gray

Aluminum Fin. S1SPFFTAL S1SPFFTBRS S1SPFFTBL S1SPFFTGY

Single Receptacle + Data

Opening for 20 or 30A Twist-Lock® receptacle (1.56" OD) and (2) keystone openings for Hubbell jacks or flush AV connectors



Hubbell DataCom + Power

(1) 20A, 125V receptacle and 3 unit recessed Hubbell iSTATION opening for data, voice and AV applications



S1SP3IM

Hubbell DataCom + Duplex

(1) duplex opening, (2) flush keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, S1SPDU2IM voice and



AV applications

Hubbell DataCom + Style Line® Decorator

(1) Style Line decorator opening, (2) flush keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications



Hubbell DataCom

1 unit flush Hubbell iSTATION opening and 3 unit recessed Hubbell iSTATION opening for data, voice and AV applications



Active Multimedia + Power

Single 20A, 125V receptacle, (2) flush keystone openings, (1) rectangular Style Line® decorator opening to accommodate active multimedia modules or low voltage outlet frames



Extron® or FSR + Power

(1) 20A, 125V receptacle, recessed opening for (3) single Extron® MAAP series adapter plates or FSR IPS plates



S1SPEXT1

Extron® or FSR + Power

(1) 20A, 125V receptacle, recessed opening for (1) single Extron MAAP and (2) single AAP series adapter plates or FSR IPS plates



Extron® or FSR Single-Service

or FSR IPS plates

Recessed opening for (2) single Extron MAAP and (2) sinale AAP series adapter plates



S1SPEXT3

Extron® AAP + Power

(1) 20A. 125V receptacle. (2) flush keystone and recessed openings for (2) single Extron AAP Series adapter plates



*Furnished with two screw-in flexible metal conduit connectors. See Section F for complete offering of Hubbell jacks and frames. See page T16 for FRPT Configuration Chart.

(2) S1FP34BL





S1FP34GY





Sub-Plate Accessories

Replacement threaded conduit plugs

S1FP34AL

	Color			
Description	Aluminum Finish	Brass Finish	Black	Gray
1½" plug	S1FP15AL	S1FP15BRS	1 S1FP15BL	S1FP15GY

See TO2 for colors/finishes; Use with S1SPFFxx and S1SPFFTxx only; Sub-plate supplied with plugs

S1FP34BRS

Decorator Frames

atalog No
S620BK
S612BK
S614BK
S616BK
S614

ScrubShield[®] Complies with UL514 A & C



Extron is a registered trademark of Extron Electronics.

3/4" plug