


5" Recessed

Fire Rated Housing



For complete fixture, order housing with trim.



New Construction Fire Rated Ceilings with E26 socket

P85-FB

Ceiling Opening: 5-1/4"
Recessed Depth: 9-1/16"
Plaster Frame: 9-9/16" x 13-1/4"
Pryouts: 1/2" and 3/4"

**See page 795 for P8555-01 IC Box to allow use in IC rated applications.*

P85-FB HOUSING FEATURES

- UL Classified to maintain fire rating of 1 hour or less for UL P500 series roof/ceiling designs.
- UL Classified to maintain fire ratings of 2 hours or less for UL D200, D500, G200, G500, L200 and L500 series floor/ceiling designs.
- Non-IC rated*.
- Fits into 2" x 10" construction.



U.S. Patent #: 5758959, 6004011, 6357891, 6254527

Trims - Non-IC

6-1/8" outside diameter, except where indicated*.



EYEBALL
P8176-28 White
*6-3/8" dia.
75w PAR-30,
short neck.



STEP BAFFLE
P8175-20 Antique Bronze
P8175-31 Black
65w BR30, 50w PAR30



STEP BAFFLE
P8175-28 White
65w BR30, 50w PAR30



OPEN
P8168-28 White
65w BR30,
50w PAR30 LN



OPEN SHOWER
P8367WL-28 White
Wet Location listed.
50w PAR30
Wet Location trims require use with outdoor rated PAR lamps



SHOWER LIGHT
P8109-60 White Glass
Wet Location listed.
Metal flange.
40w A19, 50w PAR30
Short Neck



ALZAK®
P8172-21A Clear Alzak®
85w BR30, 50w PAR30
Short Neck

5" Recessed

Housings

For complete fixture, order housing with trim.



New Construction Air-Tight IC with E26 socket

P851-ICAT

Ceiling opening: 5-1/2"
Recessed depth: 5-3/8"
Pryouts: 1/2" and 3/4"

P851-ICAT HOUSING FEATURES

- Rated for direct contact with insulated ceiling.
- Meets ASTM-E283 air flow requirements.
- Adjustable housing to accommodate ceiling thickness.
- Bar hangers with integral nail, can be installed up to 24" joists.
- Use with compatible items only.



Remodel Air-Tight IC with E26 socket

P1851-ICAT

Ceiling opening: 5-1/2"
Recessed depth: 7-3/16"
Pryouts: 1/2"

P1851-ICAT HOUSING FEATURES

- Rated for direct contact with insulated ceiling.
- Meets ASTM-E283 air flow requirements.
- Adjustable housing to accommodate ceiling thickness 1/2" to 1-1/2".



IC Trims & Non-IC Trims

6-1/2" outside diameter.



STEP BAFFLE
P868-31 Black
Damp location listed.
50w max. PAR30/R30



STEP BAFFLE
P868-28 White
50w PAR30/R30



EYEBALL
P876-28 White
75w PAR30



OPEN
P8268-21 Clear Alzak
With gasket.
Damp location listed.
50w max. PAR30/R30



OPEN
P8268-28 Satin White
With gasket.
Damp location listed.
50w max. PAR30/R30



SHOWER TRIM
P867WL-28 White
Wet location listed when used with an outdoor rated PAR30 lamp. 50w PAR30*

*WL trims require use with outdoor rated PAR lamps

LED IC Trims

LED ROUND

P8061-09-30K Brushed Nickel
P8061-20-30K Antique Bronze
P8061-28-30K White
P8061-31-30K Black
10.5w integrated LED, 3000K, 90CRI, 725 lumens.



P8061-09-30K



P8061-20-30K



P8061-28-30K



P8061-31-30K

LED EYEBALL

P8176-09-30K Brushed Nickel
P8176-20-30K Antique Bronze
P8176-31-30K White
P8176-31-30K Black
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



P8176-09-30K



P8176-31-30K



P8176-20-30K



P8176-28-30K

All fixtures:



Featuring 5" Recessed and Gust
Image: Schumacher Homes

5" Recessed

Shallow Housing

For complete fixture, order housing with trim.



New Construction Air-Tight IC and Non-IC with E26 socket

P84-AT

Ceiling opening: 5-1/4"
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 5-1/4"
Pryouts: 1/2" and 3/4"

P84-AT HOUSING FEATURES

- Shallow profile (5-1/2") for 2x6 construction.
- UL & CUL listed for damp locations & through wiring.
- Meets Washington State Energy Code requirements.
- Can be installed in ceilings from 1/2" to 1-1/2" thick.
- Notched mounting frame for easy alignment.
- Locking feature to secure housing.
- Integral T-bar clamps.
- Nail grip bar hangers accommodate up to 24" on center ceiling joists.
- Slotted interlocking bar hangers provide solid mounting on 24" centers.
- Rated for 8 #12 90 degree conductors (4 in/4 out).
- Integral Romex clamps.
- Trims are easy-in & push-lock into place.
- Adjustable lamp position.

IC Trims & Non-IC Trims

For insulated or non-insulated ceilings. 6-1/8" outside diameter, except where indicated.



SHALLOW BAFFLE
P8375-28 White
P8375-31 Black
65w BR-30, 50w PAR-30



OPEN
P8368-28 White
65w BR-30, 50w PAR-30



EYEBALL
P8176-28 White
6-3/8" dia.
75w PAR-30 Short Neck



DROP OPAL SHOWER
P8109-28 White
Wet location listed.
Metal flange.
30w R-20



OPEN SHOWER TRIM
P8367-WL28 White
Wet location listed.
50w PAR30*
** WL trims require use with outdoor rated PAR lamps*

5" Recessed

Shallow Remodel Housing

For complete fixture, order housing with trim.



Remodel Air-Tight IC with E26 Socket

P1841-ICAT

Ceiling opening: 5-1/2"
Recessed depth: 5-3/8"
Pryouts: 1/2"

P1841-ICAT HOUSING FEATURES

- Rated for direct contact with insulated ceiling.
- Meets ASTM-E283 air flow requirements.
- Adjustable housing to accommodate ceiling thickness 1/2" to 1-1/2".
- Use with compatible items only.



IC Trim

6-1/2" outside diameter. Can also be used with P851-ICAT.



SHALLOW STEP BAFFLE
P8475-28 Satin White
Damp location listed.
Lamp: PAR30/R30, 50w max.
Compatible with **P851-ICAT** and **P1841-ICAT**.



SHOWER TRIM
P867WL-28 White
Wet location listed when used with an outdoor rated PAR30 lamp. 50w PAR30*



EYEBALL
P876-28 White
75w PAR30

**WL trims require use with outdoor rated PAR lamps*

LED IC Trims

All fixtures:



LED ROUND
P8061-09-30K Brushed Nickel
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



LED ROUND
P8061-20-30K Antique Bronze
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



LED ROUND
P8061-28-30K White
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



LED ROUND
P8061-31-30K Black
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



LED EYEBALL
P8176-09-30K Brushed Nickel
10.5w integrated LED, 3000K, 90CRI, 670 lumens.



LED EYEBALL
P8176-20-30K Antique Bronze
10.5w integrated LED, 3000K, 90CRI, 670 lumens.



LED EYEBALL
P8176-28-30K White
10.5w integrated LED, 3000K, 90CRI, 670 lumens.



LED EYEBALL
P8176-31-30K Black
10.5w integrated LED, 3000K, 90CRI, 670 lumens.

LED IC Trims

All fixtures:



LED ROUND
P8061-09-30K Brushed Nickel
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



LED ROUND
P8061-20-30K Antique Bronze
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



LED ROUND
P8061-28-30K White
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



LED ROUND
P8061-31-30K Black
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



LED EYEBALL
P8176-09-30K Brushed Nickel
10.5w integrated LED, 3000K, 90CRI, 670 lumens.



LED EYEBALL
P8176-20-30K Antique Bronze
10.5w integrated LED, 3000K, 90CRI, 670 lumens.



LED EYEBALL
P8176-28-30K White
10.5w integrated LED, 3000K, 90CRI, 670 lumens.



LED EYEBALL
P8176-31-30K Black
10.5w integrated LED, 3000K, 90CRI, 670 lumens.

5" Recessed LED

LED Housings

For complete fixture, order housing with trim.



New Construction Air-Tight IC with LED Quick Connect

P84-LED

Ceiling opening: 5-1/4"
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 5-1/2"
Pryouts: 1/2" and 3/4"

P84-LED HOUSING FEATURES

- Integral quick connectors mate with P8061 and P8176 series.



Remodel Air-Tight IC with LED Quick Connect

P1841-LED

Ceiling opening: 5-1/2"
Recessed depth: 5-3/8"
Pryouts: 1/2"

P1841-LED HOUSING FEATURES

- Rated for direct contact with insulated ceiling.
- Adjustable housing to accommodate ceiling thickness 1/2" to 1-1/2" .
- Meets ASTM-E283 air flow requirements.

5" LED Round Trim

Flicker free dimming down to 10% with many Triac or forward phase dimmers. Flicker rate less than 30%.

P8061-09-30K Brushed Nickel
P8061-20-30K Antique Bronze
P8061-28-30K White
P8061-31-30K Black
10.5w integrated LED, 3000K, 90CRI, 700 lumens.



P8061-09-30K



P8061-20-30K



P8061-28-30K



P8061-31-30K

P8061 & P8176 TRIM FEATURES

- Frosted polycarbonate lens controls direct glare from LEDs.
- cULus listed for wet locations.
- Lumen output and distribution comparable to 65w BR30 incandescent lamp.
- CRI is 90+ rivaling CFL.
- Suitable for use in IC or NON-IC applications.
- 50,000 hours life based on 70% lumen maintenance (TM-21).

5" LED Eyeball Trim

Flicker free dimming down to 10% with many Triac or forward phase dimmers. Flicker rate less than 30%.

P8176-09-30K Brushed Nickel
P8176-20-30K Antique Bronze
P8176-28-30K White
P8176-31-30K Black
10.5w integrated LED, 3000K, 90CRI, 670 lumens.



P8176-09-30K



P8176-20-30K



P8176-28-30K



P8176-31-30K