Marine Products

15 Amp Twist-Lock® Devices and Accessories

15A 125V AC Twist-Lock[®] Devices



6Ð



HBL47CM00



HBL47CM20C



HBL47CM29C



HBL47CM15



Description Catalog Number Yellow duplex receptacle has heat resistant body. IP20 suitability. HBL47CM00 HBL47CM20C Yellow Insulgrip® plug has rugged nylon housing and detachable cord grip with range of .30-.69 in. (7.5-17.4) that utilizes a unique offset jaws arrangement to provide secure strain relief. IP20 suitability. Yellow Insulgrip connector body has rugged nylon housing and detachable cord grip HBL47CM29C with range of .30-.69 in. (7.5-17.4) that utilizes a unique offset jaws arrangement to provide secure strain relief. IP20 suitability. Panel mount flanged outlet has heat resistant melamine interior and stainless steel casing. HBL47CM15 IP20 SUITABILITY. Panel mount flanged inlet has heat resistant melamine interior and stainless steel casing. HBL47CM16 IP20 SUITABILITY.

Accessories Description Catalog Number Yellow Valox® spring-loaded lift cover for weatherproofing duplex receptacles. Stainless steel HBL52CM21 screws and neoprene gasket included for mounting to FS/FD type weatherproof boxes. IP20 SUITABILITY. HBL52CM21W Same as HBL52CM21 except white in color Same as HBL52CM21 except gray in color. HBL5221 HBL52CM22 Same as HBL52CM21 except for mounting to standard boxes. Same as HBL52CM22 except gray in color. HBL5222 Short yellow Seal-Tite® cover for weatherproofing HBL47CM20C Insulgrip plug when used HBL60CM23** with receptacles or connector bodies. Also can be used to weatherproof HBL47CM29C Insulgrip connector body when used with HBL47CM16 flanged inlet. IP44 SUITABILITY. HBL60CM24** Yellow Seal-Tite cover for weatherproofing HBL47CM29C Insulgrip connector body when used on extension cords and adapters. IP20 suitability.

Note: **Not UL Listed or CSA Certified.



Valox[®] is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.



