Switches

Accessories

Pilot Light, 120/277V AC Description

Red neon pilot light, back and side wired, fits standard switch wallplate.

Brass Locking Cover Attachment for Switches Available in Master Keying and Straight Keying Systems

Description	Catalog Number	
Straight keying (all locks alike). Appropriate for most applications. Straight cylinder type lock, each HBL96061 ordered operates on the same key. All locks are keyed alike.	HBL96061*	
Same as above except in dull chrome finish to match stainless steel plates.	HBL96061DCH*	
Straight keying (individual). Straight cylinder type lock, each HBL96062 ordered operates on a different key. All locks are keyed differently and individually. This type cannot be master keyed.	HBL96062*	

IP44

Catalog Number

HBL1220RJ

SWITCHOUT[®] Lockout Device

Description	Catalog Number
Yellow, nylon toggle switch lockout device (Two devices per package).	HSLDPK2*

Weatherproof Wallplates

	0 · · · · · ·
Description	Catalog Number
Clear bubble wallplate, silicone rubber for use with all general purpose AC toggle and PresSwitch [®] switches. Fits both FS/FD and standard boxes.	HBL1795
Cast aluminum lift cover with fiber shield. For standard toggle and PresSwitch® switches. Fits only FS/FD boxes.	HBL7420

Weatherproof Wallplates for PresSwitch® Switches


Description	Catalog Number
Gray neoprene PresSwitch [®] wallplate. Fits FS/FD and standard boxes.	HBL1750
Same as above except yellow.	HBL17CM50
Gray neoprene PresSwitch [®] wallplate with 125V red pilot light. Fits only FS/FD boxes.	HBL1785
Same as above except yellow.	HBL17CM85

Note: *Not UL Listed or CSA Certified.

Each locking wallplate is supplied with two keys.

See section BB for additional information on safety lockout devices. See section O for additional wallplates.

> 2.84 (72.1) 3.25° 4.56° (82.6) (115.8) (19 dia. 4 holes (4.8) HBL7420







HBL96061 Shown with cover and switch (sold separately)



ŰL

E

HSLDPK2



HBL1795



Dimensions in Inches (mm)

