



ATD2000C

Dual (Ultrasonic and Passive Infrared) Ceiling Sensors

Combines the excellent minor motion detection of ultrasonic with the outstanding passive infrared (PIR) long-range major motion detection.

Description	Voltage	Coverage Area	
		2000 sq. ft. (360°)	1000 sq. ft. (180°)
Low voltage sensor with photocell and isolated relay.	24V DC	ATD2000CRP	ATD1000CRP
Low voltage sensor.	24V DC	ATD2000C	—
Line voltage sensor.	120-277V AC	ATD2000CL	ATD1000CL



ATD1000CRP

Passive Infrared Ceiling Sensors

Outstanding long range major motion detection.

Description	Voltage	Coverage Area
		1500 sq. ft. (360°)
Low voltage sensor with photocell and isolated relay.	24V DC	ATP1500CRP
Low voltage sensor.	24V DC	ATP1500C
Line voltage sensor.	120-277V AC	ATP1500CL

Note: All Low voltage ceiling sensors must use a CU series control unit. See page E-10 for details.

Line voltage ceiling sensors suitable for occupancy (auto-on) applications only. Use low voltage ceiling sensors and low voltage switches with CU series control units (E-10) for vacancy (manual on) applications.

See pages E-25 to E-28 for technical specifications, coverage patterns and wiring schematics.

For Assembled in USA units Add suffix "U".



ATP1500C

Dual (Ultrasonic and Passive Infrared) Wall Mount Sensors

Description	Color	Coverage	Catalog Number
Low voltage sensor 32kHz with photocell and isolated relay.	Office White	1600 sq. ft.	ATD1600WRP



ATD1600WRP

Passive Infrared Wall Mount Sensors

Description	Color	Coverage	Catalog Number
Low voltage sensor with photocell and isolated relay.	Office White	1600 sq. ft.	ATP1600WRP
Low voltage sensor for aisle and high bay applications, with photocell and isolated relay.	Office White	120 linear feet	ATP120HBRP



ATP1600WRP

Note: All wall mount sensors must use a CU series control units. See page E-10 for details.

See pages E-25 to E-28 for technical specifications, coverage patterns and wiring schematics.

For Assembled in USA units Add suffix "U"

Low Voltage Switches

Single gang design, momentary or latching operation. Compatible with all Hubbell low voltage sensors and Load:Logic® Centralized and Distributed Control Systems. 100mA @ 30V DC max.

Description	Color	Catalog Number
Low voltage switch, latching, 1 button.	Ivory	DSL3011
	Light Almond	DSL30LA1
	White	DSL30W1
Low voltage switch, momentary, 1 button.	Ivory	DSM3011
	Light Almond	DSM30LA1
	White	DSM30W1
Low voltage switch, momentary, 2 buttons.	Ivory	DSM3012
	Light Almond	DSM30LA2
	White	DSM30W2



DSL30W1
DSM30W1

Note: Wallplate sold separately.