Switched Disconnects and Enclosures

CPB Series Compact Pendant Stations, Two Button, NEMA 4X

Description	Catalog Number
Single-speed normally open-normally closed without mechanical interlock.	CPB20
Single-speed with mechanical interlock between pushbuttons.	CPB21
Single-speed with mechanical interlock between pushbuttons, black housing.	CPB21BK
Two-speed with mechanical interlock between pushbuttons.	CPB22
Note: Included with product: pylon cord arin and sealing washer (must be installed to achieve NI	=MAAX rating)

Note: Included with product: nylon cord grip and sealing washer (must be installed to achieve NEMA 4X rating). Indication label pack. Cord dia. range .375-.625 in. (9.5-15.9) Ambient temperatures: 25°F to 140°F (32°C to 60°C).


Typical applications: Package electric motor hoists. Remote control of machinery.

Contact Ratings, CPB Series

Voltage	Current
120V	6A
240V	ЗA
125V	1.1A
250V	.55A
Voltage	Current
120V	ЗА
240V	1.5A
	120V 240V 125V 250V Voltage 120V

33 27 9.13" (231.9) 2.38"

CPB21




IP44

*Mechanical "floating ball" interlock prevents activating both Pushbuttons simultaneously.







Dimensions in Inches (mm)

F-29

Wiring Diagram CPB2 Series

<u>IP55</u>

PBS Series Heavy Duty Pendant Pushbutton Stations, NEMA 3R Description Catalog Number

2 button, single speed.	PBS2
2 button, two speed.	PBS22
4 button, single speed.	PBS4
4 button, two speed.	PBS42
6 button, single speed.	PBS6
6 button, two speed.	PBS62
8 button, single speed.	PBS8
8 button, two speed.	PBS82

Product Dimensions, PBS Series

Style	А	Approx. Wt. Assembled	Catalog Number
2 button	7.88" (200.0)	2.5 lbs	PBS2
4 button	13.69" (347.6)	4.5 lbs	PBS4
6 button	18.0" (457.2)	5.5 lbs	PBS6
8 button	22.31" (566.7)	7.5 lbs	PBS8

Note: Housing: Yellow vinyl rubber.

Contact Interrupting Ratings, PBS Series

Voltage	Current
120V	6A
240V	ЗA
125V	.4A
250V	.2A
Voltage	Current
120V	6A
240V	ЗA
125V	1.1A
	120V 240V 125V 250V Voltage 120V 240V