## **Floor Boxes**

ScrubShield<sup>®</sup> Complies with UL514A & C



SystemOne	Flush	Floor Boxes						4" Core Hole			
Configuration Chart			Non- Metallic			Metal		1		ted Poke-T	
Approved for use in the City of Chicago. (except S1PFB) Sub-Plates											
	Style Line <sup>®</sup> Decorator/GFCI	$\bigcirc$	S1PFB	S1CFB	S1SFB	S1SFBCR	3.5	S1SFBAVCR	S1PTFIT	S1PT4X4FIT	
S1SPDU	Duplex/Duplex		3	3.5	3.5	3.5	3.5	3.5	<b>√</b> +	×	1
S1SPDUSL	Duplex/Style Line <sup>®</sup> Decorator	ð	3	3.5	3.5	3.5	3.5	3.5	<b>√</b> +	X	1
S1SP4X4 S1SP4X4PA S1SP4X4SYS	Hubbell 4 X 4 Panduit Mini-Com <sup>®</sup> 4 X 4 SYSTIMAX <sup>®</sup> 4 X 4		4	4	4	4	4	4	~		~
S1SP4X4C S1SP4X4PAC S1SP4X4SYSC	Marked with " <sup>(1)</sup> Controlled"	0	Ð		Ð	Ð	Ð		×	<b>/</b> +	×
S1SPTL	Twist-Lock <sup>®</sup> Receptacle + Data	0	4	4	4	4	4	4	×	<b>√</b> +	X
S1SP3IM	Hubbell DataCom + Power	0	5	5	5	5	5	5	1	×	<b>√</b> +
S1SP4IM	Hubbell DataCom	0	3.5	3.5	3.5	3.5	3.5	3.5	1	X	√+
S1SPDU2IM	Hubbell DataCom + Duplex	Đ	5	5	5	5	5	5	1	X	<b>√</b> +
S1SPSL2IM	Hubbell DataCom + Style Line <sup>®</sup> Decorator	Ø	5	5	5	5	5	5	1	×	<b>√</b> +
(Carpet)	Furniture Feed Cover/Flange (Replace "xx" with BRS (Brass finish), AL (Aluminum finish), BL (Black) or GY (Gray).		3	3.5	3.5	3.5	3.5	3.5	1	×	√+
	Extron <sup>®</sup> or FSR + Power		4	4	4	4	4	4	1	X	1.
	Marked with "O Controlled"	V		$\square$	$\square$	$\square$		$\square$	•	<b>^</b>	• •
S1SPEXT2C	Extron <sup>®</sup> or FSR + Power Marked with " <sup>(1)</sup> Controlled"	C	4	4	4	4	4	4		×	<b>√</b> +
	Extron <sup>®</sup> or FSR Single-Service	0	4.5	4.5	4.5	4.5	4.5	4.5	1	×	<b>√</b> +
	Extron <sup>®</sup> or FSR + Power Marked with " <sup>(1)</sup> Controlled"		4	4	4	4	4	4		×	<b>√</b> +
	Ortronics Series II <sup>®</sup> + Power Marked with "O Controlled"	Ō	5	5	5	5	5	5	1	X	<b>√</b> +
S1SPTRAC	Ortronics TracJack <sup>®</sup> + Power	Ň	5	5	5	5	5	5	1	X	<b>√</b> +
S1SPMAX	Marked with " <sup>(1)</sup> Controlled" Siemon MAX <sup>®</sup> + Power		5	5	5	5	5	5		X	1.
S1SPAMM20	Marked with "O Controlled" Active Multimedia + Flush								•		• •
S1SPAMM20C	Keystone + Power Marked with "O Controlled"	O	5	5	5	5	5	5		X	<b>/</b> +
<b>S1CFCxx</b> (Carpet)	SystemOne Floor Boxes and FRPTs use SystemOne Universal Covers (Replace		Signifies minimum depth of concrete pour in inches for Hubbell SystemOne Floor Boxes.								
<b>S1TFCxx</b> (Tile)	"xx" with BRS (Brass finish), AL (Aluminum finish), BL (Black) or GY (Gray).		Extron <sup>®</sup> is a Mini-Com <sup>®</sup>	registered tra and Panduit <sup>®</sup>	demark of E are registere	ktron Electror d trademarks	nics. MAX <sup>®</sup> is s of Panduit ( ics <sup>®</sup> are reciv	a registered t Corp. SYSTIM, stered tradem	rademark of	The Siemon (	Company.

www.hubbell.com/wiringdevice-kellems/en

HUBBELL<sup>®</sup> Wiring Device-Kellems **O-23**