



















SystemOne Flush Sub-Plates

| Description | Catalog Number | Description | Catalog Number | Description | Catalog Number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Style Line® Decorator/GFCI (2) Style Line® decorator openings for power and/or datacom applications. |  S1SP | Duplex/Duplex (2) Duplex openings for power and/or datacom applications. |  S1SPDU | Duplex/Style Line® Decorator (1) Duplex and (1) Style Line® decorator opening for power and/or datacom applications. |  S1SPDUSL |
| Hubbell 4 X 4 (4) 20A, 125V receptacles. (4) Keystone openings for Hubbell jacks or flush AV connectors. Power can be wired as single or two circuit with isolated ground capability. Includes  stickers. |  S1SP4X4 S1SP4X4C | Carpet Furniture Feed Cover/Flange* (1) 3/4" and (1) 1 1/2" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes carpet flange. |  | Tile Furniture Feed Cover/Flange* (1) 3/4" and (1) 1 1/2" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes tile flange. |  |
| Provided with 15 ft. wire leads Provided with 30 ft. wire leads | S1SP4X415 S1SP4X430 | Aluminum Fin. Brass Finish Black Gray | S1SPFFAL S1SPFFBRS S1SPFFBL S1SPFFGY | Aluminum Fin. Brass Finish Black Gray | S1SPFFTAL S1SPFFTBRs S1SPFFTBL S1SPFFTGY |
| Single Receptacle + Data Opening for 20 or 30A Twist-Lock® receptacle (1.56" OD) and (2) Keystone openings for Hubbell jacks or flush AV connectors. |  S1SPTL | Hubbell DataCom + Power (1) 20A, 125V receptacle and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications. Marked with  |  S1SP3IM S1SP3IMC | Hubbell DataCom + Duplex (1) Duplex opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. |  S1SPDU2IM |
| Hubbell DataCom + Style Line® Decorator (1) Style Line® decorator opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. |  S1SPSL2IM | Hubbell DataCom 1 unit flush Hubbell iSTATION opening and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications. |  S1SP4IM | Active Multimedia + Power Single 20A, 125V receptacle; (2) flush Keystone openings; (1) rectangular Style Line® decorator opening to accommodate active multimedia modules or low voltage outlet frames. |  S1SPAMM20 |
| Extron® or FSR + Power (1) 20A, 125V receptacle. Recessed opening for (3) single Extron® MAAP series adapter plates or FSR IPS plates. |  S1SPEXT1 | Extron® or FSR + Power (1) 20A, 125V receptacle. Recessed opening for (1) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates. |  S1SPEXT2 | Extron® or FSR Single-Service Recessed opening for (2) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates. |  S1SPEXT3 |
| Marked with  | S1SPEXT1C | Marked with  | S1SPEXT2C | Marked with  | S1SPAMM20C |
| Extron® AAP + Power (1) 20A, 125V receptacle. (2) flush Keystone & recessed opening for (2) single Extron® AAP Series adapter plates. |  S1SPEXT4 | Ortronics Series II® + Power (1) 20A, 125V receptacle. Recessed opening for (3) 1 unit Ortronics Series II® modules. |  S1SPORT | Ortronics TracJack® + Power (1) 20A, 125V receptacle. Recessed bezel for (6) Ortronics TracJack® modules. |  S1SPTRAC |
| Marked with  | S1SPEXT4C | Marked with  | S1SPORTC | Marked with  | S1SPTRACC |
| Panduit Mini Com® 4 X 4 (4) 20A, 125V receptacles. (4) Openings for Panduit Mini-Com Connectivity. |  S1SP4X4PA S1SP4X4PAC | SYSTIMAX® 4 X 4 (4) 20A, 125V receptacles. (4) Openings for SYSTIMAX® Connectivity. |  S1SP4X4SYS S1SP4X4SYSC | Siemon MAX® + Power (1) 20A, 125V receptacle. Recessed bezel for (6) Siemon MAX® modules. |  S1SPMAX S1SPMAXC |
| Includes  | | Includes  | | Marked with  | |

Note: *Furnished with two screw-in flexible metal conduit connectors. See Network Wiring section for complete offering of Hubbell jacks, frames and datacom accessories.
See page P-30 for FRPT Configuration Chart.

Sub-Plate Accessories

| Description | | Description | Catalog Number | |
|--------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|-----------------|---------------------------------------------------------------------------------------|
| Replacement Threaded Conduit Plugs Used with S1SPFFx and S1SPFFTx only. Sub-plate is supplied with plugs. |  | Replacement for S1SPMAX . Sub-plate is supplied with data frame. Works with Siemon MAX®. | S1DFMAX |  |
| Color | 1 1/2" Plug | Replacement for S1SPTRAC sub-plate. Sub-plate is supplied with data frame. Works with Ortronics TracJack®. | S1DFTRAC |  |
| Aluminum Finish | S1FP15AL | Blank Style Line® decorator frame, Black. | NS620BK |  |
| Brass Finish | S1FP15BRS | 2-Port Style Line® decorator frame, Black. | ISF2BK | |
| Black | S1FP15BL | 4-Port Style Line® decorator frame, Black. | ISF4BK | |
| Gray | S1FP15GY | 6-Port Style Line® decorator frame, Black. | ISF6BK | |

Extron® is a registered trademark of Extron Electronics. MAX® is a registered trademark of The Siemon Company. Mini-Com® and Panduit® are registered trademarks of Panduit Corp. SYSTIMAX® is a registered trademark of CommScope, Inc. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.