tradeSELECT[®] Products

Singles, Range and Dryer Power Receptacles and Plugs

Single Receptacles, 2 Pole, 3 Wire

	Weather and	TR		WR	
Description	Tamper-Resistant	Tamper-Resistant	Standard	Weather Resistant	Standard
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 250V NEMA 6-15R	15A 250V NEMA 6-15R
Black Brown Gray Ivory Light Almond White	RR151BKWRTR RR151WRTR RR151GYWRTR RR151IWRTR RR151LAWRTR RR151LAWRTR	RR151BKTR RR151TR RR151GYTR RR151ITR RR151LATR RR151WTR	RR151BK RR151 RR151GY RR151I RR151LA RR151W	RR155BKWR RR155WR RR155GYWR RR155IWR RR155LAWR RR155WWR	RR155BK RR155 RR155GY RR155I RR155LA RR155LA RR155W
Description	Weather and Tamper-Resistant	Tamper-Resistant	Standard	Weather Resistant	Standard
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	20A 125V NEMA 5-20R	20A 125V NEMA 5-20R	20A 125V NEMA 5-20R	20A 250V NEMA 6-20R	20A 250V NEMA 6-20R
Black Brown Gray Ivory Light Almond White	RR201BKWRTR RR201WRTR RR201GYWRTR RR201IWRTR RR201LAWRTR RR201LAWRTR	RR201BKTR RR201TR RR201GYTR RR201ITR RR201LATR RR201WTR	RR201BK RR201 RR201GY RR201I RR201LA RR201W	RR205BKWR RR205WR RR205GYWR RR205IWR RR205LAWR RR205LAWR RR205WWR	RR205BK RR205 RR205GY RR205I RR205LA RR205LA RR205W

Note: See page Tech-10 for Weather and Tamper-Resistant descriptions.

Range and Dryer Power Receptacles

	30A 125/250V NEMA 14-30R	50A 125/250V NEMA 14-50R UL/CSA	30A 125/250V NEMA 10-30R UI/CSA	50A 125/250V NEMA 10-50R
Description	Flush Mount for 1- or 2-Gang Box	Flush Mount for 1- or 2-Gang Box	Flush Mount for 1- or 2-Gang Box	Flush Mount for 1- or 2-Gang Box
Rating	30A 125/250V 3 Pole, 4 Wire with Ground	50A 125/250V 3 Pole, 4 Wire with Ground	30A 125/250V 3 Pole, 3 Wire without Ground	50A 125/250V 3 Pole, 3 Wire without Ground
Black White	RR430F RR430FW	RR450F RR450FW	RR330F* —	RR350F* —
Description	Surface Mount	Surface Mount	Surface Mount	Surface Mount
Rating	30A 125/250V 3 Pole, 4 Wire with Ground	50A 125/250V 3 Pole, 4 Wire with Ground	30A 125/250V 3 Pole, 3 Wire without Ground	50A 125/250V 3 Pole, 3 Wire without Ground
Black	RR430	RR450	RR330*	RR350*
Description	Panel Mount	Panel Mount	Panel Mount	Panel Mount
Rating	30A 125/250V 3 Pole, 4 Wire with Ground	50A 125/250V 3 Pole, 4 Wire with Ground	_	_
Black	RR430PM	RR450PM	-	_

Note: *For replacement use only.

Range and Dryer Power Angled Plugs

Rating Black	with Ground RR435P	without Ground RR335P	RR435P
	30/50A 125/250V 3 Pole, 4 Wire	30/50A 125/250V 3 Pole, 3 Wire	STEP GACE
Description	30A 125/250V NEAA 1430R ULCSA With Interchangeable Blades for 30 or 50 Amp	30A 125/250V NEMA 10-30F ULCSA ULCSA With Interchangeable Blades for 30 or 50 Amp	



(YL) (SP









RR450



RR430PM



www.hubbell.com/wiringdevice-kellems/en