

## SystemOne Recessed 8 Inch Sub-Plates

### Center Plate Configurations

- Allows for 3 duplexes or up to 18 data/AV jacks. Other combinations possible
- Accepts third party AV devices (i.e. Extron<sup>®</sup>, Crestron<sup>®</sup>, FSR<sup>®</sup>)
- Standard NEMA spacing between devices













### Perimeter Plate Configurations










- Available in pre-wired duplexes or openings to accommodate third party AV devices
- Multiple duplexes can be wired in the supplied junction box or independently







### Center Sub-Plates - Single Gang

Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate
Blank cover plate		(2) Extron <sup>®</sup> MAAP openings	
<b>S1R8CSPB</b> (1) 1 unit Hubbell iSTATION opening		<b>S1R8CSPC</b> (1) 1.5 unit Hubbell iSTATION opening (See section Y for modules)	
<b>S1R8CSPD</b> (1) 1.60" opening for 20A & 30A Twist-Lock <sup>®</sup>		<b>S1R8CSPE</b> (1) Duplex opening	
<b>S1R8CSPG</b> (1) 1.40" opening for simplex or 15A Twist-Lock <sup>®</sup>		<b>S1R8CSPI</b> (1) Style Line <sup>®</sup> decorator opening	
<b>S1R8CSPJ</b>		<b>S1R8CSPK</b>	




### Perimeter Sub-Plates

Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate
Blank cover plate		Single Extron <sup>®</sup> MAAP opening	
<b>S1R8PSPU</b> Pull through with 1" bushing opening		<b>S1R8PSPV</b> Single Extron <sup>®</sup> AAP opening	
<b>S1R8PSPW</b> (1) 1 unit Hubbell iSTATION opening (See section Y for modules)		<b>S1R8PSPX</b> Dual 20A pre-wired power cubes; one circuit (Supplied with isolated ground sticker)	
<b>S1R8PSPY</b> Dual 20A pre-wired power cubes; one circuit (Supplied with isolated ground sticker); Marked with "Controlled"		<b>S1R8PSPZ</b> <b>S1R8PSPZ25</b> (25 foot leads)	
<b>S1R8PSPZC</b>			

### Center Sub-Plates - Two Gang

Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate
Two gang; (4) Extron <sup>®</sup> AAP openings		Two gang; 3 unit Hubbell iSTATION opening (See section Y for modules)		Two gang; (2) Style Line <sup>®</sup> Decorator openings		Two gang; device depth extension collar (for use with 3rd party data up to 2.5" depth)	
<b>S1R8CSPA</b>		<b>S1R8CSPL</b>		<b>S1R8CSPM</b>		<b>S1R8CSPEXT</b>	

### Center Sub-Plates - Three Gang

Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate
Three gang; blank cover plate		Three gang; device depth extension collar (for use with 3rd party data up to 2.5" depth)		Three gang extender with two gang opening; device depth extension collar (for use with 3rd party data up to 2.5" depth)	
<b>S1R8CSPN</b>		<b>S1R8CSPEXT3</b>		<b>S1R8CSPEXT32</b>	

Note: Rectangular sub-plates are for center compartments, crescent sub-plates are for perimeter compartments and are not inter-changeable. See page Q-14 for covers and accessories.

Extron<sup>®</sup> is a registered trademark of Extron Electronics.  
Crestron<sup>®</sup> is a registered trademark of Crestron Electronics, Inc.  
FSR<sup>®</sup> is a registered trademark of FSR Inc.