

MADL MADX

ordering logic

Ø24"

model											
ALEX	ANDV	CEAB	CENC	CHAN	DOMU	FLBC	FLCC	FLDC	MADL	MADX	
shaft											
											Ø3"
					Ц						Ø4"
			_					_			Ø5"
			Ш								Ø6"
											Ø7"
											Ø8"
											Ø14"
color											
											black
											bronze
											green
											white
											gray
											RAL _
ordering example											

ALEX / 4 / BB

Ø20'

specifications

construction

Post shall be made from a one-piece, seamless extruded aluminum shaft welded to a cast aluminum monolithic base. A welded ground lug is accessible through the hand hole, which shall be located on the post shaft (opposite of the opening) and concealed by a formed aluminum cover. All cast aluminum parts shall be low copper alloy A356. All extruded aluminum parts shall be alloy 6061-T6. Cast aluminum bolt covers, which are mechanically attached to the based plate, are optional for this post and should be considered when a base cover will not be used. Standard fluted shaft profile shall be 16-flat flutes for 3"OD and 12-flat flutes for 4", 5", & 6"OD.

fasteners

All fasteners shall be stainless steel. When tamper resistant fasteners are required, spanner HD (snake eye) style shall be provided (special tool required).

inish

Finish shall be Beacote V polyester powdercoat paint, electrostatically applied and thermocured. All painted surfaces shall be subjected to chemical pre-treatment prior to painting by full immersion process. Finish shall meet or exceed AAMA 2604 standards.