



ordering logic													
model													
MAIX	MERL	MERM	MERS	MERX	METR	NYCS	NYCL	TULP	VALL	VINY	WILC		
shaft													
												Ø3"	
												Ø4"	
												Ø5"	
												Ø6"	
												Ø7" Ø8"	
												Ø14"	
color													
												black	
	Ц											bronze	
												green	
												white	
												gray	
												RAL	
ordering example													
		MERL/ 4 / BB											

specifications

construction

Post shall be made from a one-piece, seamless extruded aluminum shaft welded to a cast aluminum monolithic base. A welded ground lug is accessible through the hand hole, which shall be located on the post shaft (opposite of the opening) and concealed by a formed aluminum cover. All cast aluminum parts shall be low copper alloy A356. All extruded aluminum parts shall be alloy 6061-T6. Cast aluminum bolt covers, which are mechanically attached to the based plate, are optional for this post and should be considered when a base cover will not be used. Standard fluted shaft profile shall be 16-flat flutes for 3"OD and 12-flat flutes for 4", 5", & 6"OD.

fasteners

All fasteners shall be stainless steel. When tamper resistant fasteners are required, spanner HD (snake eye) style shall be provided (special tool required).

inish

Finish shall be Beacote V polyester powdercoat paint, electrostatically applied and thermocured. All painted surfaces shall be subjected to chemical pre-treatment prior to painting by full immersion process. Finish shall meet or exceed AAMA 2604 standards.