

## **IECEx Certificate** of Conformity

### INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification System for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEx BAS 11.0071X** Page 1 of 4 Certificate history:

Issue 7 (2021-03-02) Issue 6 (2020-02-06) Issue No: 8 Status: Current

Issue 5 (2017-03-22) 2022-08-12 Date of Issue: Issue 4 (2017-01-05)

Issue 3 (2015-02-06) Applicant: **Hawke International** Issue 2 (2014-09-05) A Division of Hubbell Limited Issue 1 (2013-08-02)

A Member of the Hubbell Group of Companies Issue 0 (2011-09-02) Oxford Street West, Ashton-under-Lyne

Lancashire, OL7 0NA **United Kingdom** 

Equipment: 487 stopping plug

Optional accessory:

Type of Protection: Flameproof, Increased safety, Dust Protection by Enclosure

Marking: Ex db IIC Ex eb IIC Gb

Ex db | Ex eb | Mb

Ex tb III C Db (-60°C to +80°C, -60°C to +160°C or -60°C to 200°C) see schedule

Ex db IIC Ex eb IIC Gb Ex tb III C Db (-60°C to +80°C, -60°C to +160°C or -60°C to 200°C) see schedule when manufactured from

R S Sinclair

aluminium

Approved for issue on behalf of the IECEx

Certification Body:

Position: Technical Manager

Signature:

(for printed version)

(for printed version) 12/8/2022

1. This certificate and schedule may only be reproduced in full.

This certificate is not transferable and remains the property of the issuing body.
The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.

Certificate issued by:

**SGS Baseefa Limited Rockhead Business Park** Staden Lane Buxton, Derbyshire, SK17 9RZ United Kingdom





# IECEx Certificate of Conformity

Certificate No.: IECEx BAS 11.0071X Page 2 of 4

Date of issue: 2022-08-12 Issue No: 8

Manufacturer: Hawke International

A Division of Hubbell Limited

A Member of the Hubbell Group of Companies Oxford Street West, Ashton-under-Lyne

Lancashire, OL7 0NA United Kingdom

Manufacturing Hawke International

locations: A Division of Hubbell Limited

A Member of the Hubbell Group of

Companies

Oxford Street West, Ashton-under-

Lyne

Lancashire, OL7 0NA United Kingdom

Killark, A Division of Hubbell Inc.

(Delaware)

2112 Fenton Logistics Park Blvd.

Fenton, MO 63026

**United States of America** 

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

#### STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements

Edition:7.0

IEC 60079-1:2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"

Edition:7.0

IEC 60079-31:2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"

Edition:2

IEC 60079-7:2017 Explosive atmospheres - Part 7: Equipment protection by increased safety "e"

Edition:5.1

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

### **TEST & ASSESSMENT REPORTS:**

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

GB/BAS/ExTR11.0165/00 GB/BAS/ExTR13.0164/00 GB/BAS/ExTR14.0223/00 GB/BAS/ExTR15.0032/00 GB/BAS/ExTR16.0322/00 GB/BAS/ExTR17.0095/00

GB/BAS/ExTR19.0284/00 GB/BAS/ExTR22.0112/00

Quality Assessment Reports:

GB/BAS/QAR06.0061/09 GB/SIR/QAR16.0021/06



# IECEx Certificate of Conformity

Certificate No.: IECEx BAS 11.0071X Page 3 of 4

Date of issue: 2022-08-12 Issue No: 8

#### **EQUIPMENT:**

Equipment and systems covered by this Certificate are as follows:

The Type 487 Range of Stopping Plugs is manufactured in brass, steel, stainless steel or aluminium and is designed for the closure of unused entries in flameproof, increased safety or dust protected enclosures. The range covers sizes with metric threads from M16 to M130, other parallel thread forms of equivalent sizes, for example electrical conduit (ET), Pg, BSPP are provided.

Each plug has a threaded portion, 15mm to 20mm long as a minimum, depending on the thread type and size, and a larger circular head with a tapered shoulder. The stopping plug is manufactured with a broached hexagon hole in the larger diameter which is intended for tightening purposes. The underside of the shouldered head may be machined with a groove into which a nitrile or silicone rubber O-ring may be fitted to provide sealing to an associated enclosure.

The stopping plugs, when provided with the O rings and fitted in to suitable equipment, is capable of meeting the requirements of IP66/IP67

#### SPECIFIC CONDITIONS OF USE: YES as shown below:

- 1. The maximum operation temperature range of the stopping plug when fitted with a nitrile O-ring is -60°C to +80°C.
- 2. The maximum operating temperature range of the stopping plug when fitted with a silicone O-ring is -60°C to +160°C.
- 3. The maximum operating temperature range of the stopping plug when fitted with no O ring is -60°C to +200°C.
- 4. When the stopping plug is fitted in plain holes in increased safety or dust protected enclosures the sealing face of the enclosure is to be smooth and the hole no larger than 0.7mm above the major diameter of the male thread on the stopping plug. The stopping plug is to be secured with a locknut and optional locking washer.
- 5. When fitted in threaded holes the sealing face of the enclosure is to be smooth, the threaded hole perpendicular to the wall of the enclosure and the thread medium fit.
- 6. When the stopping plugs are used for increased safety or dust protection and no O ring is fitted the user is to ensure that the enclosure and stopping plug interface is suitably sealed, in accordance with EN 60079-14, to maintain the ingress protection rating of the associated enclosure and protection concept.
- 7. Anti-seize spray shall be applied to the stopping plug manufactured from aluminium.



# IECEx Certificate of Conformity

Certificate No.: IECEx BAS 11.0071X Page 4 of 4

Date of issue: 2022-08-12 Issue No: 8

### **DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)**

#### Variation 8.1

To confirm that the equipment covered by this certificate has been reviewed against the requirements of IEC 60079-0: 2017 and IEC 60079-7: 2015: +Amd 1: 2017 in respect to the differences from IEC 60079-0: 2011 and IEC 60079-7: 2015. None of the differences in the standards affect this equipment. The Ex marking code remains unchanged.

#### Variation 8.2

Marking modification to include associated UKEX information.

#### Variation 8.3

Description updated to include use of optional RFID tag as cover in Variation 2.

ExTR: GB/BAS/ExTR22.0112/00 | File Reference: 22/0214