



(1) EC-TYPE-EXAMINATION CERTIFICATE (Translation)

(2) Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres - **Directive 94/9/EC**

(3) EC-type-examination Certificate Number:

PTB 02 ATEX 1072



(4) Equipment: Controller type GR.. - ...L... .. CN

(5) Manufacturer: KILLARK, Div of Hubbel Inc. (Delaware)

(6) Address: St. Louis MO 63115 USA

(7) This equipment and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.

(8) The Physikalisch-Technische Bundesanstalt, notified body No. 0102 in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres, given in Annex II to the Directive.

The examination and test results are recorded in the confidential report PTB Ex 02-12231.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 50 014:1997 + A1 + A2

EN 50 018:2000

(10) If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.

(11) This EC-type-examination Certificate relates only to the design and construction of the specified equipment in accordance with Directive 94/9/EC. Further requirements of this Directive apply to the manufacture and supply of this equipment.

(12) The marking of the equipment shall include the following:




II 2 G EEx d IIC T6 or T5

Zertifizierungsstelle Explosionschutz

By order:

Dr.-Ing. U. Klausmeyer
Regierungsdirektor



Braunschweig, January 17, 2003

SCHEDULE

(13)

(14) **EC-TYPE-EXAMINATION CERTIFICATE PTB 02 ATEX 1072**

(15) Description of equipment

The controller of type GR.. - ...L... .. CN consists alternatively of one or several housings of the type of protection Flameproof Enclosure "d", which contain electrical apparatus. The connection is carried out by direct cable entry or through a conduit entry. Technical details for it are specified in the operating instructions.

Electrical data

Rated voltage max. 690 V
Conductor size AWG max. 120 mm² (4/0)

Maximum power loss for use in temperature class

| Housing Type | T6 | T5 |
|--------------|-------|-------|
| GRB | 30 W | 40 W |
| 2GRB | 35 W | 55 W |
| 4GRB | 45 W | 65 W |
| GRE | 55 W | 85 W |
| GRM | 75 W | 115 W |
| 3GRM | 90 W | 130 W |
| 5GRM | 95 W | 140 W |
| GRK | 100 W | 145 W |
| 4GRK | 145 W | 205 W |
| GRL | 120 W | 170 W |
| GRH | 160 W | 225 W |
| 4GRH | 190 W | 265 W |
| 8GRH | 230 W | 330 W |
| GRHC | 180 W | 255 W |
| 4GRHC | 220 W | 310 W |
| 8GRHC | 245 W | 355 W |
| GRHA | 215 W | 300 W |
| 4GRHA | 240 W | 345 W |
| 8GRHA | 270 W | 395 W |

Rated values are maximum values, the actual electrical values are determined by mounted electrical apparatus. Within these limiting values complying with the appropriate standards the manufacturer specifies the final limiting values dependent on power supply specifications, operating mode, utilization category, etc.

(16) Report PTB Ex 02-12231

(17) Special conditions for safe use

The controller may also be connected by means of suitable cable entries or conduit systems which meet the requirements of EN 50018, sections 13.1 and 13.2, and for which a separate examination certificate has been issued.

Openings not used shall be closed in compliance with EN 50018, section 11.

This EC type-examination certificate as well as any future supplements thereto shall at the same time be regarded as supplements for Component Certificate PTB Nr. Ex- 97.D.1048.

(18) Essential health and safety requirements

The tests and the favorable results these have produced reveal that the controller meets the requirements of directive 94/9/EC as well as those of the standards quoted on the cover sheet.

Zertifizierungsstelle Explosionsschutz

By order



Dr.-Ing. U. Klausmeyer
Regierungsdirektor



Braunschweig, January 17, 2003

1. SUPPLEMENT

according to Directive 94/9/EC Annex III.6

to EC-TYPE-EXAMINATION CERTIFICATE PTB 02 ATEX 1072

(Translation)

Equipment: Controller Type GR...L...CN

Marking: II 2 G EEx d IIC T6 or T5

Manufacturer: Killark, Div. of Hubbell Inc. (Delaware)

Address: St. Louis, MO 63113
USA

Description of supplements and modifications

Into the controller type GR...L...CN can be built in - separately certified - push button pilot lights type series GOB4 and GOL4 and pilot light type series GOB3 and GOL3.

These push button pilot lights and pilot lights are approved for the gas group IIB + H₂.
The marking changes to read:

II 2 G EEx d IIB + H₂ T6 or T5

The empty housing type GR...L...CN can be used, which is approved in the 1st supplement of EC-type examination certificate PTB 02 ATEX 1071 U.

Shock protection, protection against solid bodies,
and protection against ingress of water

IP56 according to EN 60529
as a minimum

Test report: PTB Ex 03-13345

Zertifizierungsstelle Explosionsschutz

By order:

Dr.-Ing. U. Klausmeier
Regierungsdirektor



Braunschweig, February 02, 2004

Sheet 1/1

EC-type-examination Certificates without signature and official stamp shall not be valid. The certificates may be circulated only without alteration. Extracts or alterations are subject to approval by the Physikalisch-Technische Bundesanstalt. In case of dispute, the German text shall prevail.

2. SUPPLEMENT

according to Directive 94/9/EC Annex III.6

to EC-TYPE-EXAMINATION CERTIFICATE PTB 02 ATEX 1072

(Translation)

Equipment: Controller Type GR...L...CN

Marking: II 2 G EEx d IIC T6 or T5 or EEx d IIB + H₂ T6 or T5

Manufacturer: Killark, Div. of Hubbell Inc. (Delaware)

Address: St. Louis, MO 63113
USA

Description of supplements and modifications

The type designation of the controller type GR...L...CN is supplemented. Alternatively it can be read: type GR...L...CEN.

The controller may also be used in areas in which explosive atmospheres produced by dust/air mixtures may occur.

The marking will be supplemented to:

II 2 G EEx d IIC T6 or T5 or EEx d IIB + H₂ T6 or T5

II 2 D IP66 T 80 °C or T 95 °C

Protection against foreign bodies

and ingress of liquids: IP 66 according to EN 60529

Applied standards

EN 50281-1-1:1998

Test report: PTB Ex 05-15016

Zertifizierungsstelle Explosionsschutz

By order:

Braunschweig, June 24, 2005

Dr.-Ing. U. Klausmeyer
Direktor und Professor

