

Page 1 of 2



CEI	(ISO TYPE 3 CERTIFICATION		CE		
Issued to	Killark - A Division of Hubbell Inc.				
Address	2112 Fenton Logistics Park Blvd. Fenton, MO 63026 USA				
Project Number	LR3251-2				
Product	LED Luminaires for use in Ordinary locations with optional Battery Backup, Reflectors (Domed type and Angle)				
Model Number	WMBLX Series, and Reflectors (Dome	WMBLX Series, and Reflectors (Domed type and Angle).			
		*WMBLX Series is followed by alphanumeric suffixes denoting electrical and mechanical variations. (See Nomenclature breakdown below)			
Ratings	Input: 120-277 VAC 50/60Hz, 377-480	Input: 120-277 VAC 50/60Hz, 377-480 Vac 50/60Hz, 105-250 Vdc			
Environmental ratings	Type 4X enclosure, IP 66, Marine Rated (US Only) T _{amb} : -40°C to 55°C (Standard Version). T _{amb} : -20°C to 40°C (Battery Backup Version)				
Applicable Standards	Standard Number CAN/CSA-C22.2 No. 250.0-17 CAN/CSA-C22.2 No. 94.2 CAN/CSA-C22.2 No. 250.13:20 UL 50E UL 1598 UL 1598A UL 1598A UL 8750 ANSI/IEC 60529:2004	Edition 5 th 2 nd 2020 5th 1 st 2nd R2011	Date 2017 2015 2020 2020 2021 2000 2021 2011		
Factory/Manufacturing Location	Killark - A Division of Hubbell Inc. 2112 Fenton Logistics Park Blvd., Fen	ton, MO 63026 U	SA		
	pment identified in this Certificate and described in the elevant requirements of the above referenced standa the provisions of OPS's Service Agreement.				
IMPORTANT NOTE In order to maintain integrity of the QPS Mark (1) Compliance with the above-mentione			Notice (QSD 55) issued ir	ו future – is not maintained, or	
Issued By: Scott Airdrie					
Signature:		Date	e: March 28, 2025		



The SCC and IAS Accreditation Symbols are official symbols of the respective accreditation bodies, used under license. 81 Kelfield St., Unit 8, Toronto, ON, M9W 5A3, Canada Tel: 416-241-8857; Fax: 416-241-0682 www.qps.ca



Page 2 of 2



NOMENCLATURE:

The complete luminaire catalog number is as follows:

Example: Cat. No. WMBLX 6 iE1 30 A 2 G.00 2 3 4 56 7 1 1-Series Designation-MBLX (Series Constant). 2-Lumen Output in 1000s of Lumens 1 - 1000 lm, 2 - 2000 lm, 4 - 4000 lm. 6 - 6000 lm 3-Battery Backup (optional) - iE05—500 Lumen (180 Min) - iE1 - 1000 Lumen (90 Min) 4-Voltage - Input supply 30 -120 thru 277 VAC, 50/60 Hz 33 -347 thru 480 VAC, 50/60 Hz 34 – 105 thru 250 VDC 5-Mounting Splice Box Α-Pendant В-Wall Х-Ceiling D -Stanchion 25° 6-Entry Size Blank-no splice box 2 - ¾" NPT 3 - 1" NPT 4 - 1 ¼" NPT 5 - 1 ½" NPT 7-Options YYZZ - White LED Chromaticity where YY= correlated color temperature (CCT) minimum 3000K; ZZ= Color Rendering Index (CRI) maximum 95 (No value=Standard 5000K CCT 70 CRI minimum) AR – Angled Reflector (MBLXAR)

DR – Dome Reflector (MBLXDR)

SP – Add Supplemental Surge Protection

- TBx -- Terminal Blocks (may be alphanumeric to indicate terminals)
- xH Optional Paint (i.e. RH = Red Housing)
- Guard
- G With Guard
- N No Guard



