

# CERTIFICATE OF COMPLIANCE

Certificate Number 20190402-E195978  
Report Reference -19611127  
Issue Date 2019-APRIL-02

Issued to: RACO  
3902 W SAMPLE ST, PO BOX 4002  
SOUTH BEND IN 46634-4002

This certificate confirms that  
representative samples of METALLIC OUTLET BOXES  
See Addendum Page

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 514A & CSA C22.2 NO. 18.1-13,  
Standard for Metallic Outlet Boxes

Additional Information: See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any Information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

Certificate Number 20190402-E195978  
Report Reference 19611127  
Issue Date 2019-APRIL-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL - Flush device boxes, Cat. Nos. @500, 503, @504, 505, 506, and 592.

Outlet boxes, Cat. Nos. 161(a), 172, and 181; with clamps for nonmetallic sheathed cable, nonmetallic flexible tubing, armored cable, metal clad interlocking armor cable and flexible metal conduit.

Covers for outlet box, Cat. Nos. 737, 811,

USL/CNL - Covers for outlet box, Cat. Nos. 768, 818, 819, 820, 829, @832(a), @833(c), 835, @837 through 841, 843, 870RAC, 856, 857, 858, 876, and 972, 881RAC.

(a) - May be followed by up to 9 alphanumeric characters for packaging, color, mounting, marking, customer identification, multilingual labeling/instructions and commercial variations.

(c) - May be followed by -0, -3 or -5.

@ - May be prefixed by 8.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

