



RSPX.E12145 Receptacles with Plugs Interlocked with Switches for Use in Hazardous Locations

[Page Bottom](#)

Receptacles with Plugs Interlocked with Switches for Use in Hazardous Locations

[See General Information for Receptacles with Plugs Interlocked with Switches for Use in Hazardous Locations](#)**HUBBELL INC (DELAWARE) - VANTAGE DIVISION**

E12145

4140 World Houston Pky, Ste 130
Houston, TX 77032 USA

Class I, Group D; Class II, Groups F and G.

YX Series Switches with integral receptacles and Series PX plugs:

Poles	Amps	V	HP	V
3 (2-wire)	20	250, ac or dc	2	230, ac
			2	250, dc
3 (2-wire)	30	250, ac or dc	2	230, dc
			1	460, ac
4 (3-wire)	15	250, ac or dc	2	230, ac
			2	460, ac
4 (3-wire)	30	250, ac or dc	2	230, ac
	20	460, ac	2	460, ac

Last Updated on 2017-02-13

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".