



GAI-TRONICS®
A HUBBELL COMPANY

751-002 24 V DC Speaker Amplifier

Confidentiality Notice

This manual is provided solely as an installation, operation, and maintenance guide and contains sensitive business and technical information that is confidential and proprietary to GAI-Tronics. GAI-Tronics retains all intellectual property and other rights in or to the information contained herein, and such information may only be used in connection with the operation of your GAI-Tronics product or system. This manual may not be disclosed in any form, in whole or in part, directly or indirectly, to any third party.

The following are trademarks of GAI-Tronics Corporation:

SmartSeries®

Page/Party®

ADVANCE

SmartVolume™

General Information

The Model 751-002 24 V dc Speaker Amplifier is an important component of the 700 Series Page/Party system. It mates directly with the 701 and 751 Series Enclosures and broadcasts page announcements over the Page/Party system speakers.

The Model 751-002 is constructed of 16-gauge cold-rolled steel and is suitable for either indoor or outdoor use.




Figure 1. Model 751-002 Speaker Amplifier
(shown with an indoor enclosure)

Installation

⚠ CAUTION ⚠ —Do not install this equipment in hazardous areas or areas other than those on the equipment approval list in the “Approvals” section. Such installation may cause a safety hazard and consequent injury or property damage.

To install, plug the Model 751-002 Speaker Amplifier into the appropriate enclosure, and tighten the four screws in the corners of the front panel. Refer to Figure 1 for typical installation details.

Maintenance

Adjustment

Model 751-002 Speaker Amplifier mates with an enclosure wired directly to a speaker. The speaker volume adjustment is located under the GAI-Tronics nameplate on the front panel. Refer to **Error! Reference source not found.** Use a small flat-blade screwdriver to adjust the speaker sound volume.

Troubleshooting

The following table lists some hints to aid technicians in troubleshooting:

Problem	Solution
Feedback/distortion (a hum or buzz on the line) occurs during all Page/Party station operation.	The line may be improperly terminated. Inspect the system cable for loose connections, shorts, and grounds. Line balance assembly connections are critical.
Associated speaker level requires adjustment.	Adjust the speaker volume control located on the amplifier front panel, behind the nameplate. Refer to Error! Reference source not found. Use a small standard screwdriver to perform these adjustments.

Replacement Parts

Part Number	Description
10440-002	Maintenance Cable
46101-012	Screw Kit
12523-001	GAI-Tronics Nameplate Kit
12601-001	Standoffs (10 pack)
12604-004	Fuse, Slow-Blow, 2 A (10 pack)
25210-005	Gasket
69701-012	Speaker Amplifier PCBA

Specifications

Input voltage	21–28.8 V dc range, 25 V dc nominal
Power consumed	zero signal: 0.25 W maximum signal: 27 W
Construction/finish.....	16-gauge cold-rolled steel/gray polyurethane
Amplifier output.....	push-pull, Class B, 12 W (minimum), with nominal supply voltage
Amplifier sensitivity	0.5 V ac, for rated output
Frequency response.....	250–4,000 Hz, +0/–3 dB ref. to 1 kHz
Distortion	1% maximum THD @ 1 kHz, 12 W
Input impedance.....	50,000 Ω (nominal)

Controls..... speaker volume (adjusted through an access hole
 behind the nameplate on the front panel)
 Temperature range -22 °F to +158 °F (-30 °C to +70 °C)
 Dimensions 8.1 H × 8.1 W × 3.0 D in; (206 × 206 × 76 mm)
 Shipping weight 5.6 lb (2.6 kg)

Approvals

NRTL Listed for USA and Canada..... Class I, Div. 2, Groups A, B, C, D
 when used with listed GAI-Tronics Model 702 or 703 24 V dc series enclosures
 Class I, Div. 2, Groups A, B, C, D
 Class II, Div. 2, Groups F and G;
 Class III, Div. 2, when used with listed
 GAI-Tronics Model 732, 758, 7325, 733, or 7335 24 V dc series enclosures

Warranty

Equipment. GAI-Tronics warrants for a period of one (1) year from the date of shipment, that any GAI-Tronics equipment supplied hereunder shall be free of defects in material and workmanship, shall comply with the then-current product specifications and product literature, and if applicable, shall be fit for the purpose specified in the agreed upon quotation or proposal document. If (a) Seller's goods prove to be defective in workmanship and/or material under normal and proper usage, or unfit for the purpose specified and agreed upon, and (b) Buyer's claim is made within the warranty period set forth above, Buyer may return such goods to GAI-Tronics nearest depot repair facility, freight prepaid, at which time they will be repaired or replaced, at Seller's option, without charge to Buyer. Repair or replacement shall be Buyer's sole and exclusive remedy. The warranty period on any repaired or replacement equipment shall be the greater of the ninety (90) day repair warranty or one (1) year from the date the original equipment was shipped. In no event shall GAI-Tronics warranty obligations with respect to equipment exceed 100% of the total cost of the equipment supplied hereunder. Buyer may also be entitled to the manufacturer's warranty on any third-party goods supplied by GAI-Tronics hereunder. The applicability of any such third-party warranty will be determined by GAI-Tronics.

Services. Any services GAI-Tronics provides hereunder, whether directly or through subcontractors, shall be performed in accordance with the standard of care with which such services are normally provided in the industry. If the services fail to meet the applicable industry standard, GAI-Tronics will re-perform such services at no cost to buyer to correct said deficiency to Company's satisfaction provided any and all issues are identified prior to the demobilization of the Contractor's personnel from the work site. Re-performance of services shall be Buyer's sole and exclusive remedy, and in no event shall GAI-Tronics warranty obligations with respect to services exceed 100% of the total cost of the services provided hereunder.

Warranty Periods. Every claim by Buyer alleging a defect in the goods and/or services provided hereunder shall be deemed waived unless such claim is made in writing within the applicable warranty periods as set forth above. Provided, however, that if the defect complained of is latent and not discoverable within the above warranty periods, every claim arising on account of such latent defect shall be deemed waived unless it is made in writing within a reasonable time after such latent defect is or should have been discovered by Buyer.

Limitations / Exclusions. The warranties herein shall not apply to, and GAI-Tronics shall not be responsible for, any damage to the goods or failure of the services supplied hereunder, to the extent caused by Buyer's neglect, failure to follow operational and maintenance procedures provided with the equipment, or the use of technicians not specifically authorized by GAI-Tronics to maintain or service the equipment. **THE WARRANTIES AND REMEDIES CONTAINED HEREIN ARE IN LIEU OF AND EXCLUDE ALL OTHER WARRANTIES AND REMEDIES, WHETHER EXPRESS OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.**

Return Policy

If the equipment requires service, contact your Regional Service Center for a return authorization number (RA#). Equipment should be shipped prepaid to GAI-Tronics with a return authorization number and a purchase order number. If the equipment is under warranty, repairs or a replacement will be made in accordance with the warranty policy set forth above. Please include a written explanation of all defects to assist our technicians in their troubleshooting efforts.

Call 800-492-1212 (inside the USA) or 610-777-1374 (outside the USA) for help identifying the Regional Service Center closest to you.