



For technical assistance call: 281-445-7400

WARNING: THE QUICK STAB SERIES IS NOT DESIGNED FOR INTERRUPTING CURRENT. DO NOT CONNECT OR DISCONNECT THE CIRCUIT WHILE LIVE.


Application Information

Quick Stab Series connectors have been designed to safely distribute 2000 Amps @ 1000 Volts AC or DC power. These connectors are rated for 2000 Amps continuous operation at 125°C.

Installation of Quick Stab Panel Mounts

1. Drill mounting pattern as shown below into a non-ferrous panel of 0.50 inch minimum thickness.
2. Install Panel Mount into non-ferrous panel using appropriate hardware.

Mounting Pattern:



For technical assistance call: 281-445-7400

WARNING: THE QUICK STAB SERIES IS NOT DESIGNED FOR INTERRUPTING CURRENT. DO NOT CONNECT OR DISCONNECT THE CIRCUIT WHILE LIVE.

Application Information

Quick Stab Series connectors have been designed to safely distribute 2000 Amps @ 1000 Volts AC or DC power. These connectors are rated for 2000 Amps continuous operation at 125°C.

Installation of Quick Stab Panel Mounts

1. Drill mounting pattern as shown below into a non-ferrous panel of 0.50 inch minimum thickness.
2. Install Panel Mount into non-ferrous panel using appropriate hardware.

Mounting Pattern:

