Surface-mount Enclosures

Model 238 Series and Model 236 Series



GAI-TRONICS offers a variety of enclosures designed to permit surface mounting of our ***flush-mount RED ALERT® and Industrial Telephones. These enclosures provide weather-proof protection for the telephone electronics and are aesthetically appealing.

Our **236 series** enclosure offers hooded protection from the elements and is available in three standard colors; black, red, and yellow (custom colors available). These enclosures are manufactured from non-corrosive aluminum and protected with a Polyurethane finish.

Our **Model 238** series enclosures combine aesthetics and durability in a brushed stainless steel design.

All of our surface-mount enclosures are suitable for indoor and outdoor use. The 236 series and Model 238-001 enclosures are designed to accommodate our full-size telephones and are compatible with our Model 231-002 Pole Mount Kit. The Model 238-001FS is designed to accommodate our compact (FS) series telephones and utilizes our Model 231-001FS Pole Mount Kit. Model 238-003 (not shown) accommodates our flush-panel behavioral-health telephones with model numbers containing BH that measure $8.5 \, \text{H} \times 7.5 \, \text{W}$ inches; compatible with Model 231-001FS Pole Mount Kit.





Model 238-001FS (For Compact Series Telephones)



Model 238-001 (For Full-size Telephones)



Model 236-001YL (Yellow)*







Surface-mount Enclosures

Model 238 Series and Model 236 Series



SPECIFICATIONS

Model 236 Series (Full-size Telephones)	
Construction	
Finishing	Polyurethane paint
Mounting	Four 5/16-inch (0.312) diameter mounting holes in mounting bosses
Dimensions	.3 H \times 10.31 W \times 6.37 D inches; (312 \times 262 \times 162 mm), maximum (top of shroud)
Cable Entry	customer-provided

Model 238-001 (Full-size Telephones)

Construction	
Finishing	Brushed and passivated
Mounting	Four 5/16-inch (0.312) diameter mounting holes in mounting bosses
Dimensions	12.13 H \times 10.18 W \times 2.65 D inches (308 \times 259 \times 67 mm) maximum
Cable Entry	1-inch entry in rear of enclosure
Shipping Weight	5.0 lbs. maximum
Installation Manual*	Pub. 42004-434

Model 238-001FS (Compact FS Series Telephones)

Construction	
Finishing	Brushed and passivated
Mounting	Four 5/16-inch (0.312) diameter mounting holes in mounting bosses
Dimensions	8.5 H \times 6.5 W \times 2.56 D inches (215 \times 165.1 \times 65.0 mm) maximum
Cable Entry	(2) 7/8-inch entries in rear or bottom of enclosure (seals provided)
Shipping Weight	
Installation Manual*	Pub. 42004-434

Model 238-003**

Construction	304 Stainless steel, 0.063-inch thickness
Finishing	Brushed and passivated
Mounting	Four 1/4-inch (6.4mm) diameter mounting holes in mounting bosses
Dimensions	
Cable Entry	(2) 0.86-inch entries in rear or bottom of enclosure (seals provided)
Shipping Weight	
Installation Manual*	Pub. 42004-539





Tel: +(65) 6282 2242 (Press 4 for GAI-TRONICS) www.gai-tronics.com Tel: 011-61-28-851-5000 Fax: 011-61-29-899-2490 www.austdac.com.au













^{*} Manuals can be located on our website homepage at www.gai-tronics.com

^{**} Flush-panel behavioral-health telephones with model numbers containing BH that measure 8.5 H imes 7.5 W inches