



## RECOMMENDED CRIMP TOOLS AND DIES FOR HUBBELL TERMINATION CONNECTORS

Connector Code	Nominal Crimp Barrell O.D.	CONDUCTOR SIZE (ALUMINUM ONLY)		EEI	CSA	Anderson Versa-Crimp (Crimps)			BURNDY (Crimps)			BLACKBURN (Crimps)		KEARNEY (Crimps)		KEARNEY (Crimps)	
		Stranded/Compressed	Compact/Solid			VC6-350	VC6	VC6-FT	INDEX	HAND	HYD	HAND	HYD	HAND	HYD	HAND	HYD
A22	0.650"	#2 - #1	#1 - 1/0	8A	22	(2)	(2)	(2)	BG or 243	W-BG (2)	U-BG (1) U-243	5/8 (4)	--	5/8 (4)	5/8 (2)	TU (2)	52 (1)
A24		1/0	2/0														
A25	0.906"	2/0	3/0	11A	--	(4)	(3)	(3)	K840 249	W-K840 (6) W-249 (2)	U-249 (2)	840 (6)	B-49EA (2)	840 (6)	840 (4)	TX (6)	76 (2) 76H (4)
A26		3/0	4/0														
A27		4/0 - 250	250														

**NOTES:**

- Wire Brush conductor before inserting into compression connector
- Make sure to completely insert the conductor into the connector
- Do not crimp above the knurled line on the connector
- ( ) Indicates the minimum number of crimps without overlapping indents
- Rotate each successive indent 90° or 180° to prevent bowing



## CABLE ACCESSORIES

1850 Richland Ave. East • Aiken, SC 29801 • Phone: 573-682-5521 • Fax: 573-682-8714  
 E-mail: [hpsliterature@hps.hubbell.com](mailto:hpsliterature@hps.hubbell.com) • Website: <http://www.hubbell.com>

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.