

FLEXMO ORDER FORM

Solid State Motor Operator



What brand/type of switch is this motor operator being used on? (Ex: USCO AVR vertical break switch)

What is the voltage rating of the switch?

What is the current rating of the switch?

Which cabinet/enclosure material would you like?

Powder coated galvanized steel

Aluminum

Stainless steel

**Which DC voltage do you require for the motor operator?
All FlexMO motor operators use 120VAC incoming power.**

1. Direct Substation DC Voltage	48VDC	125VDC
2. FlexMO with self-contained batteries	24VDC	48VDC
3. Are you going to use an RTU with this FlexMO?	Yes	No
4. Will the RTU be mounted in the FlexMO cabinet?	Yes	No
If yes, would you like Hubbell to purchase the RTU? We will mount it and wire it for you.	Yes	No

If you would like Hubbell to purchase the RTU, please provide the RTU manufacturer, RTU name, and RTU catalog ID. (Ex: SEL, SEL-2411, SEL-241102B3BOXOXOX0130) If you would like to purchase and mount the RTU yourselves, we will provide a pre-wired RTU harness.

RTU Manufacturer

RTU Name

RTU Catalog ID

If you have any questions on ordering a FlexMO, please call Customer Service at 573-682-5521.



hubbellpowersystems.com

For product inquiries, please contact your local sales representative or customer service representative.

©2021 Hubbell Incorporated.
Because Hubbell has a policy of continuous product improvement,
we reserve the right to change design and specifications without notice.
Printed in the U.S.A. | TD_10_257_E