

Temporary Industrial Lighting







Temporary Industrial Lighting





Hubbell Wiring Devices' line of temporary lighting products offers solutions for industrial jobs or any application that requires flexible and dependable illumination. The full offering includes a wide range of products in construction site lighting, industrial work lights, explosion proof lighting, confined space entry lights, and cord reels. From LED task lights to machine maintenance lights to portable battery packs, we have the products you want built with the quality you expect from Hubbell. Durable and built for longevity, our devices provide the safety and reliability essential at any industrial job site. Whether it's a hand light, cordless or wide area light, Hubbell has what you need.

Construction Sites




Work Areas



Explosion-Proof Confined Spaces







Maintenance and Work Lights

Choose Hubbell industrial work lights for maximum user safety. The fluorescent lights are designed with all electrical components located inside a closed chamber for your protection. Lamps stay cool while spreading light over large areas. Work light models can be paired with an adjustable hanging kit or magnetic mounts for positioning flexibility. Portable work lights can be transported and re-mounted. Long cords allow free movement in work space.

LED Maintenance Work Lights

| Description | Outlet Rating | Rating | Wattage | Lumen Output | Cord Type | Cord Length | Catalog Number |
|--|------------------|----------|---------|-----------------|------------|----------------|----------------|
| LED Industrial maintenance light | N/A | 15A 125V | 28 | 2928 | 16/3 SJEOW | 25 ft. | HBLML2825L |
| LED work light with end light feature | N/A | 15A 125V | 9 | 920/120 | 18/2 SJTOW | 25 ft. | HBLWL25LED |
| LED work light with end light feature & tool tap | 12 Amp | 15A 125V | 9 | 920/120 | 16/3 SJTOW | 25 ft. | HBLWL25LEDT |

Fluorescent Maintenance Work Lights

| . | | | | | | | |
|---|------------------|----------|---------|-----------------|------------|----------------|----------------|
| Description | Outlet Rating | Rating | Wattage | Lumen Output | Cord Type | Cord Length | Catalog Number |
| Fluorescent work light with straight blade plug | N/A | 15A 125V | 13 | 825 | 16/3 SJTOW | 25 ft. | TW25F1 |
| Fluorescent work light with Twist-Lock® plug and tool tap | 12 Amp | 20A 125V | 13 | 825 | 16/3 SJTOW | 25 ft. | TW25F2 |
| Fluorescent maintenance light, 34.5 in. | N/A | 15A 125V | 50 | 3750 | 16/3 SJEOW | 25 ft. | HBLML5025 |
| Fluorescent maintenance light, 48.5 in. | N/A | 15A 125V | 25 | 2125 | 16/3 SJEOW | 25 ft. | HBLML2525 |
| Fluorescent work light, 45 in. | N/A | 15A 125V | 25 | 2125 | 16/3 SJTOW | 25 ft. | HBLWL2525 |

| Accessories and Replacement Items | |
|--|----------------|
| Description | Catalog Number |
| Magnetic mounting bracket for ML style lights, 82 lb. capacity | HBLMLMM |
| Magnetic mounting bracket for WL style lights, 58 lb. capacity | HBLWLMM |
| Replacement rough service fluorescent bulb for 13 watt style lamps | HBLREPPFB |
| Metal halide replacement bulb, 400 watts | HBLREP400MH |
| Metal halide replacement bulb, 1,000 watts | HBLREP1000MH |
| Replacement LED panel fixture, 90 LEDs, 450 lumen | HBLREP450LED |
| 5 base LED string only, 50 ft., 18/2 | HBLREP182S50 |
| 10 base LED string only, 100 ft., 18/2 | HBLREP182S100 |



Mounting Bracket

for ML Style Lights

Clip Bracket for LED String Fixtures





for WL Style Lights



Heavy Duty Metal Guard Work Light

Fluorescent



Plastic Guard for Temporary Light Strings





-

LED Industrial Maintenance Light







100



Construction Site Lighting

Hubbell's outdoor approved construction site lighting line includes both heavyduty metal halide lights and light strings for working in rugged environments. The metal halide fixtures feature extremely strong and compact heads with bulbs rated to last 10,000 hours. All frames are powder-coated yellow for safety and are constructed of a durable 1.25 inch, 12 gauge steel tube.

We have light strings for all applications in a variety of models as well as a choice of metal or plastic guards. Light sockets are spaced 10 feet apart and all sockets, plugs, and connectors are molded for added durability. In addition, the highly impact-resistant material makes for easy transportation and storage when not in use. Bulbs can be incandescent, fluorescent or LED. Consider choosing LED lighting for a durable bulb that saves energy, provides instant illumination and are rated to last 50,000 hours.

Metal Halide and LED Lights

| Description | Rating | Watts | Lumen Output | Cord Lengt | h Catalog Number |
|--|----------|-------|--------------|------------|------------------|
| 5 -10 ft. metal halide cart light with portable detachable ballast | 15A 125V | 1,000 | 110,000 | _ | HBLMH1000 |
| 6 -12 ft. metal halide cart light | 15A 125V | 2,000 | 220,000 | _ | HBLMH2000 |
| High bay metal halide light with wire guard | 15A 125V | 400 | 29,000 | Зft. | HBLMHHB400 |
| | 15A 125V | 120 | 14,000 | 5 ft. | HBLLEDHB120 |
| High bay LED light with wire guard | 15A 125V | 100 | 12,000 | 5 ft. | HBLLEDHB100 |
| | 15A 125V | 60 | 7,200 | 5 ft. | HBLLEDHB60 |



LED Light



High Bay Metal Halide Light



100W High Bay LED Light



LED Stringer Lights



Straight Blade Light String

Fluorescent Light String Straps not Shown

| Description | Fixtures | Rating | Cord Type | Lumen Output | Cord Length | Catalog Number |
|---|----------|----------|--------------|--------------|-------------|----------------|
| 90 LEDs per fixture, light string with magnetic base included | 1 | 15A 125V | 18/2 SJTW | 450* | 20 ft. | HBL182S20LED |
| | 5 | 15A 125V | 18/2 SJTW | 450* | 50 ft. | HBL182S50LED |
| 90 LEDs per fixture, light string | | 15A 125V | 18/2 SJTW | 450* | 100 ft. | HBL182S100LED |
| | 1 | 15A 125V | 18/2 SJTW | 1,100* | 20 ft. | HBL182S20LEDH |
| 60 LEDs per fixture, light string with magnetic base included | | 15A 125V | 18/2 SJTW | 1,100* | 50 ft. | HBL182S50LEDH |
| 28W High power LED light string with inline ON/OFF switch | _ | 15A 125V | 16 AWG SJTOW | 2,928 | 6 ft. | HBLLS2834 |
| Magnetic clip bracket for LED string fixtures | _ | _ | _ | _ | _ | HBLSTMC |

A Type (Edison) Twist-Lock[®] and Straight Blade Light Strings


| Description | Max Watts** | Rating | Cord Type | Fixtures | Cord Length | n Catalog Number |
|--|-------------|----------|-----------|----------|-------------|------------------|
| | 150 | 20A 125V | 12/3 STW | 10 | 100 ft. | HBL123S100PT |
| Twist-Lock [®] light string; plastic guards | 150 | 20A 125V | 12/3 STJW | 10 | 100 ft. | HBL123SJ100PT |
| Twist-Lock [®] light string; metal guards | 150 | 20A 125V | 12/3 STW | 10 | 100 ft. | HBL123S100MT |
| Straight Blade light string; plastic guards | 150 | 15A 125V | 14/2 STJW | 10 | 100 ft. | HBL142SJ100PS |
| | 150 | 15A 125V | 12/3 STW | 10 | 100 ft. | HBL123S100PS |
| | | 15A 125V | 12/3 STJW | 10 | 100 ft. | HBL123SJ100PS |
| Straight Blade light string; metal guards | 150 | 15A 125V | 12/3 STW | 10 | 100 ft. | HBL123S100MS |
| Straight Blade light string; plastic guards | 150 | 15A 125V | 12/3 STW | 5 | 50 ft. | HBL123S50PS |
| Straight Blade light string; metal guards | 150 | 15A 125V | 12/3 STW | 5 | 50 ft. | HBL123S50MS |
| Replacement plastic guard for temporary light strings | _ | _ | _ | _ | _ | HBLSTPG |
| Replacement heavy duty metal guard for temporary light strings | _ | _ | _ | _ | _ | HBLSTMG |

Max watts per fixture. HBL142SJ100PS light strings are rated for 1875 Watts total. The total wattage must be considered when daisy chaining lights strings to each other

| Wattage | Rating | Cord Type | Lumen Output | Cord Length | Catalog Number |
|---------|----------|---------------|----------------------------|----------------------------------|--|
| s 50 | 15A 125V | 16 AWG SJTOW | 3,750 | 6 ft. | HBLFS5035 |
| s 25 | 15A 125V | 16 AWG SJTOW | 2,125 | 6 ft. | HBLFS2549 |
| | s 50 | s 50 15A 125V | s 50 15A 125V 16 AWG SJTOW | s 50 15A 125V 16 AWG SJTOW 3,750 | s 50 15A 125V 16 AWG SJTOW 3,750 6 ft. |







Explosion-Proof/Confined Space Lighting and Cord Reels

For hazardous locations, bring yourself some peace of mind with Hubbell's explosion proof lighting line and confined space lighting. We offer both fluorescent and incandescent light bulbs, as well as an automatic shut off switch on hand lamps. Low voltage confined space entry lights can be water resistant, watertight, or explosion proof for a variety of job sites.

For more light where you need it, consider our cord reels with attached hand lamps. With choices such as incandescent, fluorescent, and LED lamps, more light can be brought to more places, small or large. The cord reels, complementary to the end lamps, are constructed of durable, corrosion-resistant steel to last through the toughest jobs and the desired cord length is automatically maintained through a positive-latch mechanism.

Explosion Proof/Confined Space Lighting

Hazardous Location Lights

| Description | Wattage | Lumen Output | Cord Type | Cord Lengt | th Catalog Number |
|---|---------|--------------|------------|------------|-------------------|
| Fluorescent, Class 1, Div 1 Groups C & D, Class 2, Div 1 Groups F & G, 12V, inline transformer | 26 | 1800 | 16/3 SOW | 60 ft. | HBLXF6012V |
| Incandescent, Class 1, Div 1, Groups C & D, 12V, inline transformer | 75 | 720 | 16/3 SOW | 60 ft. | HBLXI6012V |
| Fluorescent, Class 1, Div 1 Groups C & D, Class 2, Div 1 Groups F & G, 120V, less plug | 26 | 1800 | 16/3 SOW | 50 ft. | HBLXF50120V |
| Incandescent, Class 1, Div 1 Groups C & D, 120V less plug | 100 | 1230 | 16/3 SOW | 50 ft. | HBLXI50120V |
| Fluorescent, non-explosion proof, wet location, 12V, inline transformer | 13 | 825 | 18/2 SJTOW | 60 ft. | HBLWT6012V |



Incandescent Hazardous Location Light



Cord Reels

Cord Reel with Hand Lamps

| Description | Wattage | Lumen Output | Light Amps / Outlet Amps | Volts | Cord Type | Cord Lengt | h Catalog Number |
|---|-----------|--------------|-----------------------------|-------|------------|------------|------------------|
| Reel with LED hand lamp, with flashlight end, white | 9 | 920/120 | 0.065 / N/A | 125 | 18/2 SJTOW | 40 ft. | HBLC40182LED |
| Reel with non-metallic incandescent hand lamp and automatic shut off switch, yellow | 75 Max | 1150 Max | N/A / N/A | 125 | 16/3 SJT | 25 ft. | HBLC25163AIN |
| Reel with metallic incandescent hand lamp with receptacle, yellow | 75 Max | 1150 Max | N/A / 10 | 125 | 16/3 SJT | 25 ft. | HBLC25143IN |
| Reel with fluorescent hand lamp and automatic shut off switch, white | 13 | 825 | 0.3 / N/A | 120 | 18/2 SJTOW | 40 ft. | HBLC40182AFL |
| Reel with fluorescent hand lamp and inline receptacle, white | 13 | 825 | 0.3 / 12 | 120 | 16/3 SJT | 40 ft. | HBLC40163FL |



HUBBELL





Hubbell Temporary Power Solutions



Construction sites, outdoor events and other harsh environments need to ensure maximum safety when providing temporary electrical power for equipment and lighting, especially since these applications involve frequent plug-ins and disconnects. Hubbell temporary power distribution systems come in a variety of device types for protecting people against electrical shock in a wide range of applications and job sites.

| Watertight Devices | Portable Outlet Boxes | Spider Boxes | Single Pole |
|---|---|---|---|
| Hubbell offers an extensive line of plugs, connectors, receptacles and accessories rated to withstand harsh and wet environments. | Portable Outlet Boxes provide a safe rugged portable enclosure that can be used in many applications and complies with NEC [®] 110.12 regarding unused cable openings in metallic boxes. | This Heavy Duty UL Type 3R metallic enclosure incorporates the most advanced ground fault module technology for safety as well as watertight straight blade and Safety- Shroud [®] Twist-Lock [®] receptacles. | Hubbell's Single Pole connectors are UL Type 4X Rated and made from a specially formulated thermoplastic elastomer (TPE) that resists cracking in cold, hot or oily conditions as well as any other harmful environments. |

Dependable Power Solutions for Construction Sites, Work Areas and Harsh Environments



www.hubbell.com/wiringdevice-kellems/en

