



LMC™ Crane Controls

Retrofits & New Installation

Bridge & Trolley Motor Controls up to 200HP

Solid-State IGBT Control

of series-wound DC motors delivers high torque at startup, adjustable speed points and acceleration / deceleration ramps, electric braking and elimination of all contactor problems

Easy Retrofit Installations

- Connect existing power cables
- Connect existing motor cables
- Connect existing brake cables
- Connect existing operator controls
- Fine-tune pre-set acceleration ramps, speed points and braking

Save Energy Costs

Motor energy consumption reduced up to 50% plus torque boost at startup is 7 amps in the motor for every 1 amp drawn from the power source—motors work easier and last longer

Save Maintenance Costs

Solid-state construction, no wear components plus microprocessor control of contactors means contactors never make or break a load

LMC Crane Control Technology Eliminates problems caused by

- Brownouts and discontinuity of the power supply
- Substantial negative ring of supply voltages
- Positive-going transients caused by switching off other machines



Typical Travel Drive--Logic, 5-Speed Card, IGBT Power Section and Contactor Panel

Additional Benefits

- Open architecture panel design
- All components easily accessible
- Fault register for easy troubleshooting
- Hand-held data terminal for setup, changes in setup and diagnostics
- Works with Series Brakes and/or Shunt Brakes—specify when ordering
- Duplex & Quadraplex Available

Typical Specifications:

- **Voltage:** 230 VDC Nominal, 300 VDC Max, 120 VDC min
- **DC Mill Motor Frame:** 402, 602 through 614
- **Ambient Operating Temperature:** +50°C Maximum to -10°C Minimum
- **High Temperature Controls Available:** +60°C Maximum to -10°C Minimum
- **Diagnostics & Parameter Adjustment** – Data Terminal, Part No. A62499
- **Dynamic Braking Resistor:** required but not included, reuse existing units in good condition

Manufactured by:

Cableform Inc.

— 8845 Three Notch Road — Troy, Virginia 22974 — U.S.A.

Tel: 434/589-8224 — Fax: 434/589-3803 — Email: sales@OICSystems.com — www.cableform.com

Specifications subject to change without notice.

© 2009, Cableform, Inc.