

# Exposed Work Covers

Device support in exposed work applications



## 4" SQUARE, CRUSHED CORNER COVERS - RAISED 1/2"

Cat. No.	Description	Cu. In. (CM <sup>3</sup> )	Std. Pkg	Bar Coded
800C	1 Toggle Switch	6.5 (106.5)	10	050169999721
801C	1 Receptacle 1.406" Dia.			050169999745
803C	2 Toggle Switches			050169999752
804C	Blank, No Holes			050169999783
805C	1 Toggle Switch and 1 Receptacle 1.406" Dia.			050169999790
806C	1 Duplex and 1 Receptacle 1.406" Dia.			050169999813
807C	2 Receptacles 1.406" Dia.			050169999820
808C	1 GFCI			050169999837
808U	1 GFCI, 3-in-1 Plates			050169978085
809C	2 GFCI			050169999844
809U	2 GFCI, 6-in-1 Plates			050169978092
810C	30A-50A Receptacle 2.141" Dia.			050169999851
811C	30A Locking 1.719" Dia.			050169999868
811U	1 Round Device: 1.406", 1.620" or 1.719" Dia.			050169978115
812C	20A Receptacle 1.620" Dia.			050169999875
813C	30-60A Receptacle 2.625" Dia.			050169999882
814C	1 GFCI and 1 Toggle Switch			050169999899
831C	1 Duplex, 1 20A, 1.620" Dia.			050169999943
902C	1 Duplex Receptacle			050169999950
906C	1 Duplex Receptacle and 1 Toggle Switch			050169999967
907C	2 Duplex Receptacles			050169999974
915C	1 GFCI and 1 Duplex Receptacle			050169999981

## FEATURES

- Exposed work covers include screws and nuts where required
- Exposed work covers meet the requirements of the 2020 NEC Article 250.146 (A)
- No bonding jumper is required for covers with: (1) Crushed corners (2) Two or more device attachment fasteners that are permanent with thread-locking, screws, or nut-locking means (3) Insulating retaining washer removed for at least one device attachment screw
- Printed catalog number, compliances and installation instructions

## APPLICATIONS

RACO's surface covers are used to support switches or receptacles in areas where the box is surface mounted or positioned in exposed work applications.

