



1 UNCONTROLLED COPY WHEN PRINTED

ACCESS 3D PDF **CLICK HERE**

ACCESS 3D PORTAL **CLICK HERE**

NOTES:

- TO OBTAIN FITTINGS WITH GALV. STEEL HARDWARE. CHANGE LAST TWO DIGITS OF CAT. NO. TO G1, G2, ETC. (EXAMPLE-GC-141-G1 = GC-141-01 WITH GALV. HDWE.)
- MATERIAL: CASTINGS: COPPER ALLOY 2. HARDWARE: STAINLESS STEEL
- BOLT LENGTH PROVIDED FOR CONNECTING TO A .250" BAR, WHEN LONGER BOLTS ARE REQUIRED ADD PLATE THICKNESS AFTER CAT. NO. EXAMPLE - GC-141-01-1/2 = BOLT LENGTH FOR .500" PLATE
- FOR ALUM, CONNECTOR, ADD PREFIX 'A' TO CAT NO, EXP.-AGC-141-G1, ASSEMBLY WILL BE FURNISHED WITH GALV. STEEL HARDWARE
- CABLE RANGE FOR AGC-141-G1 IS #4STR TO 2/0 STR ALUMINUM CABLE
- ITEMS WITH "WOR" SUFFIX HAVE WRENCH CLEARANCE AROUND BOLT HEAD 6. EXAMPLE: GC-141A-02-WOR
- FOR PARTS TO BE SUPPLIED WITH BELLEVILLE WASHER ADD "BW" SUFFIX TO CAT. NO. (EXAMPLE: GC141A02BW)
- GC14101AP HAS WRENCH CLEARANCE AROUND BOLT HEAD
- ITEMS WITH "ED" SUFFIX ARE SUPPLIED WITH SILICON BRONZE HARDWARE
- ADD "TP" SUFFIX FOR TIN PLATED CASTINGS

| CATALOG NUMBER | CABLE | DIMENSION IN INCHES | | | | | | | | |
|----------------|---------|---------------------|-------|-------|-------|------|------|------|-------|--|
| | MIN. | MAX. | Α | В | С | J | K | L | Н | |
| GC-141-01 | #6 SOL | 2/0 STR. | 1.250 | 1.563 | 2.000 | .500 | .250 | | | |
| GC-141-01-AP | #6 SOL | 2/O STR. | 1.625 | 1.563 | 2.000 | .500 | .250 | | | |
| GC-141A-02 | #4 SOL | 300 MCM | 1.500 | 1.938 | 2.125 | .500 | .250 | | 1.281 | |
| GC-141-03 | 300 MCM | 500 MCM | 2.000 | 2.500 | 2.375 | .500 | .250 | | | |
| GC-141-04 | 500 MCM | 800 MCM | 1.875 | 2.750 | 2.750 | .500 | .250 | | | |
| GC-141-05 | 800 MCM | 1000 MCM | 2.000 | 2.875 | 3.000 | .500 | .250 | | | |
| GC-141-06 | #4 SOL | 2/O STR. | 1.688 | 1.688 | 2.125 | .625 | .250 | | | |
| GC-141-07 | #4 SOL | 300 MCM | 1.688 | 2.063 | 2.250 | .625 | .250 | | | |
| GC-141-08 | 300 MCM | 500 MCM | 2.188 | 2.563 | 2.500 | .625 | .250 | | | |
| GC-141-09 | 500 MCM | 800 MCM | 2.188 | 2.813 | 2.625 | .625 | .250 | | | |
| GC-141-10 | 800 MCM | 1000 MCM | 2.188 | 2.938 | 3.375 | .625 | .250 | | | |
| GC-141-00 | #8 SOL | #4 STR. | 1.375 | 1.375 | 2.000 | .375 | .250 | | | |
| GC-141-11 | 1000MCM | 1250 MCM | 2.500 | 3.250 | 3.875 | .625 | .250 | | | |
| GCB-141-01 | #4 SOL | 2/O STR. | 1.500 | 1.625 | 2.000 | .500 | .250 | .656 | | |
| GCB-141-02 | #4 SOL | 300 MCM | 1.500 | 2.000 | 2.125 | .500 | .250 | .656 | | |
| GC-141-3-01 | #6 SOL | 2/O STR. | 1.625 | 2.000 | 1.750 | .375 | .250 | | | |

| 210615009225 | 6/15/2021 | HG | HG | PTB | | M | (<i>DINI</i>) | JIIDD | | DAWED | ()(| TEM | C = I | nΛ | |
|---|-----------|--------|--|---|------------------------------|--|-----------------|-------|--------------|-------|-------|--------|-------|------|--|
| EC # | DATE | CHG BY | CKD BY | APPD BY | | POVER : | LYSTEMS, Inc. | IUDD | [LL | LAMEU |)II | JIEWJ, | | Inc. | |
| DESC OF DVGI INTERACTIVE CUSTOMER DRAWING FIXED C DIMENSION | | | | THIRD ANGLE PROJECTION CONFIDENTIAL: THIS DRAWING AND ITS CONFERTS ARE CONFIDENTIAL AND THE | | COPPER ALLOY GROUND CLAMP CABLE TO FLAT | | | | | | | | | |
| | | | | EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS, NO PUBLICATION, | CATALOG NUMBER: GC141 FAMILY | | | | | | | | | | |
| | | | DISTRIBUTION, OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT | SIZE DWG NO. | | PART / ASSY NO. | | | | | REV | | | | |
| REASON (S) FOR CHANGE: | | | OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS | C | C-2564 | | | | | | | 19 | | | |
| DISPOSITION OF MAT'L: | | | | UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS. | SCALE: | NS | DRN BY: | CW | DATE: 3/16/5 | 6 | SHEET | 1 DF | 1 | | |

WI-ENG-105 031319-R0