



CAT. NO.	CABLE RANGE		DIE REF.	DIMENSIONS IN INCHES				
	MIN.	MAX.		A	K	L	W	T
CCLS-325-B	0.292	0.325	0.640	2.25	0.38	5.87	1.50	0.31
CCLS-398-B	0.355	0.398	0.840	2.75	0.38	6.50	1.50	0.38
CCLS-447-B	0.414	0.447	0.840	2.75	0.38	6.50	1.50	0.38
CCLS-502-B	0.464	0.502	0.840	2.75	0.38	6.50	1.50	0.38
CCLS-563-B	0.502	0.563	1.000	3.00	0.38	6.75	1.50	0.50
CCLS-642-B	0.586	0.642	1.000	3.00	0.38	6.75	1.50	0.50
CCLS-684-B2	0.666	0.684	1.125	3.25	0.63	7.00	2.00	0.50
CCLS-743-B2	0.721	0.743	1.125	3.25	0.63	7.00	2.00	0.50
CCLS-814-B2	0.772	0.814	1.250	3.50	0.63	7.38	2.00	0.50
CCLS-883-B2	0.846	0.883	1.468	3.88	0.38	7.75	2.00	0.50
CCLS-953-B2	0.879	0.953	1.468	3.88	0.38	7.75	2.00	0.50
CCLS-1031-B2	0.953	1.031	1.468	3.88	0.38	7.75	2.00	0.50
CCLS-1081-B2	1.026	1.081	1.625	3.88	0.38	8.00	2.00	0.63
CCLS-1152-B2	1.092	1.152	1.625	3.88	0.38	8.00	2.00	0.63
CCLS-1216-B2	1.140	1.216	1.625	3.88	0.38	8.00	2.00	0.63

- NOTES:**
- MATERIAL: ALUMINUM ALLOY
  - BARREL IS FACTORY INHIBITED AND ENTIRE CONNECTOR IS SEALED IN A PLASTIC BAG.
  - A BONDED COPPER LINER MAY BE ORDERED FOR THE BOTTOM SIDE OF TONGUE BY ADDING "L" TO CATALOG NUMBER. EXAMPLE: CCLS-1031-B2-L
  - TO OBTAIN AN ANGLED TONGUE, ADD 15,30,45, OR 90 TO THE END OF THE CATALOG EX) CCLS-447-B-45

78445	5/6/2019	HG	HG	PTB
EC #	DATE	CHG BY	CKD BY	APPD BY
DESC OF DWG: REDRAWN IN NEW AUTOCAD FORMAT, ADDED NOTE 4				
REASON (S) FOR CHANGE: --				
DISPOSITION OF MAT'L: --				

THIRD ANGLE PROJECTION

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION, OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.

**HUBBELL® POWER SYSTEMS**

TITLE: ALUMINUM COMPRESSION TERMINAL CCLS SERIES B AND B2 PAD

CATALOG NUMBER: CCLS

SIZE: B	DWG NO.: CC-14256	PART / ASSY NO.: SEE TABLE	REV: 01
---------	-------------------	----------------------------	---------

SCALE: NS    DRN BY: TBW    DATE: 10/22/08    SHEET 1 OF 1