		4		2		4		•	2	1	1	
Γ		7		<u> </u>			STANDARD			ITEM	DESCRIPTION	MATERIAL
	ATALOG NUMBER	DESCRIPTION	DIM A	DIM B	DIM C	APPROX. WT. EACH	PACK			1	TOP CASTING	TIN PLATED BRASS
F	VIII 1 4716	FOR USE ON 1/4" TO 7/16" STRANDED STATIC WIRE	1.13	1.41	0.46	0.171	100			2	FLANGE BOLT, 5/16"-18X1"	SILICON BRONZE
	KUL14716	AND #8-2/0 COPPER WIRE.	[28.70]	[35.81]	[11.68]	[0.078]	100			3	BOTTOM CASTING	TIN PLATED BRONZE
D		"A"———————————————————————————————————		"B"								
D			2	•								
В						3		"C				
	& WEIGHT LBS. 2. RATINGS: A. TORQUE F	RATING: 180 INLBS	l. LBS. [N.m],		7909:	3 07/03/19	HD	RG		HUE	** HIRRFII* PO	WER SYSTEMS
A	3. CERTIFICATION A. UL CERTII 4. SUFFIXS & VARI	S, SPECIFICATIONS, & STANDARDS:	ACH CASTING			WG: C-TEMPLATE) FOR CHANGE:	CHG BY	RESP ENG	HPS CONFIDENTIAL: THIS DRAWING AND ITS CONTECTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS	POWER SY TITLE SIZE	WG NO. CC-23639 SEE CHA SCALE DRN BY JES DATE OF	AMP SY NO. REV