


2

ITEM	DESCRIPTION	MATERIAL
1	TOP CLAMP	ALUMINIUM (ADC12)
2	BOTTOM CLAMP	ALUMINIUM (ADC12)
3	3/8-16 HEX SQUARE NECK FLANGE	STAINLESS STEEL
4	3/8-16 WASHER	STAINLESS STEEL
5	3/8-16 HEX NUT	SILICON BRONZE







3D VIEW

## NOTES:

- ALL DIMENSIONS FOR REFERENCE ONLY.
  DISTANCE IN. [MM], FORCE LBS. [kN], TORQUE IN. LBS. [N.m], & WEIGHT LBS. [KG].
- 2. MATERIAL: SEE TABLE
- 3. CONDUCTOR RANGE: .#6 AWG (DIA 0.162 [4.114]) MIN 1/0 AWG (DIA 0.324 [8.252]) MAX

-	20-09-2023	RHR	SP	SP			HUBBEL	® HH	RRFII POW	ER SYSTEMS,	Inc 📶	
EC#	DATE	CHANGED BY	CHECKED BY	APPROVED BY	_		POWER SYSTEM		DDLLL I OVV	LICOTOTEMO		C MOTION CO., INC.
EC DESCRIPTION: WEIGHT (Ibma						THIRD ANGLE	TITLE					
0.274						PROJECTION	CONNECTOR					
					CONFIDENTIAL:							
			THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS, NO		CATALOG NUMBER: EM-1BCG-01FPL							
					PUBLICATION, DISTRIBUTION OR COPIES MAY		SIZE DWG NO.			PART / ASSY NO.		REV
			BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER	В	EM-1	IBCG-01FPL-CC	EM-1BCG-01	FPL	Α			
ADDITIONAL (	COMMENTS:				SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS		SCALE:	NTS	DRN BY: RHR	DATE: 20-09-2023	SHEET	1 OF 1

В