




ITEM	DESCRIPTION	MATERIAL
1	FIXED PLATE	ALUMINUM BRONZE
2	MOVEABLE PLATE	ALUMINUM BRONZE
3	7MM NON-BREAKAWAY BOLT WITH VIBRASEAL	SILICON BRONZE
4	.41" FLAT WASHER	BRASS-TIN PLATED
5	#10-32 HEX HEAD SCREW	SILICON BRONZE

- NOTES:**
- ALL DIMENSIONS FOR REFERENCE ONLY.
DISTANCE IN. [MM], FORCE LBS. [kN], TORQUE IN. LBS. [N.m], & WEIGHT LBS. [KG].
 - MATERIAL: SEE TABLE
 - CABLE RANGE: #22 AWG (DIA. 0.0253 [0.6451]) MIN-
#6 AWG (DIA. 0.162 [4.1148]) MAX

-		PREM	SP	SP	 THIRD ANGLE PROJECTION	 HUBBELL POWER SYSTEMS, Inc.  <small>POWER SYSTEMS, Inc. ELECTRIC MOTION CO., INC.</small>			
EC #	DATE	CHANGED BY	CHECKED BY	APPROVED BY		TITLE GROUND ROD CLAMP WITH CONNECTOR			
EC DESCRIPTION:				WEIGHT (lbmass) 0.393		CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS			
ADDITIONAL COMMENTS:					SIZE B	DWG NO. EM-4DBV22-CC	PART / ASSY NO. EM-4DBV22	REV A	
SCALE: NTS		DRN BY: PREM		DATE: 10/3/2023		SHEET 1 OF 1			