



RECOMMENDED TORQUE:
480 IN.-LBS.

- NOTES:
1. MATERIAL: CLAMP BODY & KEEPER: ALUMINUM ALLOY
COTTER PIN: STAINLESS STEEL
CLEVIS PIN, U-BOLTS, NUTS, WASHERS: GALV. STEEL
 2. DIMENSIONS IN INCHES.
 3. WEIGHT: 2.8 LBS.
 4. 25,000 LBS. ULTIMATE STRENGTH

<p>ANDERSSON TOLERANCE CHART</p>		<p>CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE CONTENTS HEREON ARE NOT TO BE REPRODUCED, COPIED, OR PUBLISHED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</p>	
<p>HUBBELL POWER SYSTEMS</p>		<p>HUBBELL POWER SYSTEMS</p>	
<p>TITLE HIGH STR. ALUM. SUSPENSION CLAMP</p>		<p>DO NOT SCALE THIS DRAWING</p>	
<p>SIZE B</p>	<p>DWG NO. CUTSHEET</p>	<p>CAT / PART / ASSY NO. HAS-118-N</p>	<p>REV B</p>
<p>DRN BY PTB</p>	<p>DATE 1/22/13</p>	<p>SHEET 1 OF 1</p>	