





NOTES:

- 1. HEAT IS PROVIDED BY (2) 90WATT, 120V SINGLE PHASE HEAT TRACE TAPES. FOR UNHEATED VERSION REPLACE THE PREFIX "H" WITH AN "L".
- 2. FOUR INTERNAL BRACKETS AND CONCRETE ANCHORS ARE SUPPLIED WITH THE ENCLOSURE.
- 3. FOR RECOMMENDED SLAB SIZE ADD 9" [229] TO THE ENCLOSURE EXTERIOR.
- 4. THIS ENCLOSURE IS DESIGNED WITH A FLIP UP LID & A FOLDABLE/REMOVABLE FRONT FOR EASE OF MAINTENANCE AND TESTING.

5. OLD P/N: DF2.75H

5. Jan 5, 5. 25 15. 7 535										
DIMENSIONS ARE IN INCHES OR MILLIMETERS IN BRACKETS UNLESS OTHERWISE NOTED.										
550	BY KP€	DATE	WEIGHT 140# 64kg	HU			ş	ACKSON 04-786		TC Foc
CHK	NF6	9/25/09	SCALE	DRAWING DESCRIPTION					S REV	
ENG			1*=1'	HOT BOX [®] ALUMINUM ENCLOSURE						Α
APR			SIZE							
APR			B							9/09
PROJ	ECT NU	SHEET	1	OF	1		DRAWING NUMBE HD022060042	R		