

- 1. CONNECTOR OPTICAL, MECHANICAL AND ENVIRONMENTAL PERFORMANCE MEETS TIA/EIA-568-C.3 SPECIFICATIONS.
- 2. CONNECTOR USES A UPC RADIUS TIP ZIRCONIA CERAMIC FERRULE.

В

- 3 .CONNECTOR HOUSING IS INJECTION MOLDED ENGINEERING PLASTIC RESIN.
- 4. OPTICAL INSERTION LOSS AND RETURN LOSS TEST DATE INCLUDED IN EACH BAGGED PATCH CORD.
- 5. CABLE MARKINGS TO IDENTIFY EACH END (A OR B).
- 6. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

						П	DIMENSIONING AND TOLERANCE PER ANSI Y14.5M-1982 UNLESS OTHERWISE SPECIFIED,	PROJECT REFERENCE: NPD-00160	Hubbell Premise Wiring
						eated on AUTOCAD	DIMENSIONS ARE IN INCHES (MM). TOLERANCES .XX = ±.01 (.25) .XXX = ±.005 (.127) .XXXX = ±.0025 (.0635) ANGLE TOL ±1° IN ACCEPTING OUR DRAWINGS, BLUEPRINTS, OR SUPPORTING DOCUMENTATION FOR QUOTATION OR OTHER PURPOSES, YOU AGREE	DRAWN BY: J.RUOT-JACKSON 9/20/16 CHECKED BY:	HUBBELL INCORPORATED (Delaware) 23 Clara Dr., Suite 103, Mystic, Connecticut 06355 TITLE: FIBER OPTIC PATCHCORD, OFNR, SINGLEMODE, LC/APC-LC/APC, SIMPLEX SIZE DRAWING NO. REV.
1	21494	09/20/16	INITIAL RELEASE	JJRJ	MMA	NOT TO DISCLOSE TO OTH THE IDEAS, INFORMATION DESIGNS SHOWN HEREIN THAT YOU WILL MAKE NO	NOT TO DISCLOSE TO OTHERS THE IDEAS, INFORMATION, OR		C HWS14688C 1
REV.	ECN	DATE	DESCRIPTION	CHG BY	APPD BY		THAT YOU WILL MAKE NO USE OF SAME WITHOUT PERMISSION	APPROVED BY:	SCALE: 1/1 SHEET 1 OF 1