





-12.0 ± .5

M-14179

1

| LIST OF PARTS | | | |
|-----------------|-----------------|-------------|---|
| DESCRIPTION | MATERIAL | FINISH |)IME |
| ENCLOSURE | THERMOPLASTIC | TEXTURED | NSIO |
| END CAP | THERMOPLASTIC | TEXTURED | S NC |
| PLUG BLADES & | BRASS | - | 苗 |
| GROUND PIN | | | DIMENSION SHEET FOR CAT. NO SEE TABL |
| SCREWS | STEEL | ZINC PLATED | Hi R |
| BUSHING 3PC SET | SILICONE RUBBER | - | CAT. NO. TABLE |
| (NOT SHOWN) | | | |
| GOTCHA-RING | | | |
| 3PC SET | THERMOPLASTIC | - | |
| (NOT SHOWN) | | | |
| CORD | THERMOPLASTIC | - | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

GFPST5266C AND GFPST5266CY

CORD #14 AWG TYPE SJTW-A

CORD CONNECTOR BODY NEMA 5-15R

GFPST1C (GFPST5266CY WITH CORD INSTALLED) THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE. DIMENSIONS ARE IN INCHES [mm].

TITLE

GFCI AM/PD PLUG



WIRING DEVICE-KELLEMS
HUBBELL INCORPORATED
SHELTON, CT

M-14179

TOLERANCES UNLESS
OTHERWISE SPECIFIED
.XX = ± .01
.XXX= ± .005
ANGLE TOL. ±2'

DR. BY MV SCALE 2:3

CHK. BY KP DATE 4/19/22

CAGE CODE 74545