

VIEW B TRI-TAP CONNECTOR



VIEW A
SINGLE TAP
CONNECTOR

LIST OF PARTS					
DESCRIPTION	MATERIAL	FINISH			
HOUSING	THERMOPLASTIC	BLACK			
BLADES	BRASS				
GROMMET	ELASTOMER	BLACK			
STRAIN RELIEF	STEEL	ZINC PLATED			
SCREWS	STEEL	ZINC PLATED			
CORD	PVC	YELLOW			
RECEPTACLE	THERMOPLASTIC	BLACK			

NOTES:

1. 12/3 SJTW YELLOW CABLE 300V 150 °C MAX/90°C MIN DRY, 60°C WATER RESISTANT, UL LISTED FOR US AND EITHER cULus OR CSA CERTIFIED FOR CANADA.

- FLEXIBLE IN COLD WEATHER
- RESISTANT TO CHEMICALS
- UV WITHSTAND
- ARC/FLAME RETARDANT
- 2. ALL DIMENSIONS ARE IN INCHES [mm].

CAT.#	DESCRIPTION	CONNECTOR VIEW
GFPILST15125A	15A 120V, INLINE GFCI, SINGLE TAP, AUTO	А
GFPILST15125TRIA	15A 120V, INLINE GFCI, TRI-TAP, AUTO	В

TECHNICAL:

RATED VOLTAGE: 120 VAC

OPERATING VOLTAGE RANGE: 85% TO 110% OF RATED.

CURRENT: UP TO 15 AMPS. FREQUENCY: 60Hz.

TRIP LEVEL: 5mA ± 1mA;

PHASE: SINGLE.

RESPONSE TIME: 25 mS MAX AT 500 ohm FAULT.
DIELECTRIC WITHSTAND: 1,500VRMS ACROSS CONTACT;

4,000 VRMS BETWEEN CONDUCTORS AND ENCLOSURE

SURGE WITHSTAND: 4KV/2KA PER IEC 61000-4-5 OPERATING TEMPERATURE RANGE: -35°C TO +66°C.

LEAKAGE CURRENT @93% HUMIDITY: ZERO. OVERLOAD CURRENT: 90 AMPS, 0.45 PF

RF NOISE SUSCEPTIBILITY: NORMAL OPERATION WITH 0.5 VRMS INJECTED ON POWER LINE WITH

FREQUENCIES UP TO 230 MHz.

LET GO LINE VOLTAGE: 60% OF RATED.

GROUNDED NEUTRAL DETECTION: 2 OHMS OR LESS.

CAGE CODE 74545

GENERAL:

CONSTRUCTION: COMMERCIAL GRADE DESIGN.

TYPE: CLASS A SELF TESTING POWER-UP TYPE: AUTOMATIC.

ENDURANCE: 3,000 OPERATIONS MINIMUM.

OPEN NEUTRAL PROTECTION: TRIPS UPON LOSS OF NEUTRAL. GROUNDED NEUTRAL PROTECTION: TRIPS IF GROUND AND NEUTRAL

CONNECT AT LOAD SIDE.

POWER ON INDICATION: LIGHTED GREEN LED.

ENCLOSURE: RAIN PROOF, 3R MOUNTING TYPE: PORTABLE.

WIRING APPLICATION: 3 WIRE SINGLE PHASE (HOT, NEUTRAL, GROUND)

SWITCH INTERFACE: DOUBLE INSULATED LATCHING MECHANISM: ELECTROMAGNETIC

FALSE TRIP DUE TO IMPACT: NONE AGENCY APPROVAL: c-UL-us

1	NEW RELEASE PER DCN#230920033470. D.LI		9/5/23	W
REV	DESCRIPTION	APP	DATE	

THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE. DIMENSIONS ARE IN INCHES [mm].

TITLE

15A 120VAC 2FT. INLINE GFCI ASSY W/MOLDED CONNECTOR, AUTO RESET



WIRING DEVICE-KELLEMS
HUBBELL INCORPORATED
SHELTON, CT

TOLERANCES UNLESS
OTHERWISE SPECIFIED
.XX = ± .01
.XXX= ± .005
ANGLE TOL. ±2

DR. BY D.LI SCALE 1 / 4
CHK. BY DATE 1/11/21

M-14341