



FLOOD WASHABLE SILICONE RUBBER HOUSING

| | | |
|----------------------------|-------|-------------------|
| STRIKE DISTANCE | ----- | 49 IN |
| LEAKAGE DISTANCE | ----- | 126 IN |
| SCL | ----- | 2960 LB (13.2 kN) |
| RCL | ----- | 1480 LB (6.6 kN) |
| DRY 60 HZ FLASHOVER | ----- | 515 kV |
| WET 60 HZ FLASHOVER | ----- | 450 kV |
| WET 60 HZ WITHSTAND | ----- | 380 kV |
| IMPULSE CRITICAL POSITIVE | ----- | 770 kV |
| IMPULSE WITHSTAND POSITIVE | ----- | 730 kV |
| IMPULSE CRITICAL NEGATIVE | ----- | 880 kV |
| IMPULSE WITHSTAND NEGATIVE | ----- | 835 kV |
| WEIGHT | ----- | 50 LB |

ELECTRICAL CHARACTERISTICS IN ACCORDANCE WITH ANSI C29.1-1988

Program Revision

REV DATE 04/02/18

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.



HUBBELL® POWER SYSTEMS

TITLE
QUADRI*SIL LINE
POST SERIES 250

| | | | |
|---------------------------|----------------------|---------------------------------------|--------------|
| SIZE S | DWG NO. ER_250-QP | CAT / PART / ASSY NO. P250048S0030 | REV 11 |
| DO NOT SCALE THIS DRAWING | DRN BY NON | DATE 08/27/07 | SHEET 1 OF 1 |