


FLOOD WASHABLE SILICONE RUBBER HOUSING

STRIKE DISTANCE	-----	63 IN
LEAKAGE DISTANCE	-----	253 IN
SCL	-----	2410 LB (10.7 kN)
RCL	-----	1205 LB (5.4 kN)
DRY 60 HZ FLASHOVER	-----	625 kV
WET 60 HZ FLASHOVER	-----	535 kV
WET 60 HZ WITHSTAND	-----	450 kV
IMPULSE CRITICAL POSITIVE	-----	970 kV
IMPULSE WITHSTAND POSITIVE	-----	920 kV
IMPULSE CRITICAL NEGATIVE	-----	1070 kV
IMPULSE WITHSTAND NEGATIVE	-----	1015 kV
WEIGHT	-----	59 LB

ELECTRICAL CHARACTERISTICS IN ACCORDANCE WITH ANSI C29.1-1988

Program Revision  
 REV DATE 06/04/18

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.

 <b>HUBBELL® POWER SYSTEMS</b>			
TITLE <b>QUADRI*SIL LINE          POST SERIES 250</b>			
SIZE	DWG NO.	CAT / PART / ASSY NO.	REV
S	ER_250-QP	P250060E0020	11
DO NOT SCALE THIS DRAWING	DRN BY NON	DATE 08/27/07	SHEET 1 OF 1