



CATALOG NUMBERING DESCRIPTION

W= MADE IN USA ONLY M= MADE ANYWHERE

AMP RATING (SEE TABLE)

TYPE QH FUSELINK
QH- SOLID HEAD
QHA- REMOVABLE HEAD

OPTIONS:
W/ SUFFIX 23= 23" LG (OVERALL LENGTH)
W/ NO SUFFIX= 26" LG (OVERALL LENGTH)

PACKING OPTIONS
BP

CATALOG NUMBER EXAMPLE

M15QH23
15 AMP 23" OVERALL LENGTH

AMP RATING	"A" DIA	"B" DIA	"C" DIA	"D" DIA	"L" DIM
1 THRU 20	.50	.75	.311	.090	5.50
25 THRU 30	.50	.75	.311	.125	5.50
40 THRU 50	.50	.75	.311	.141	5.50
60	.75	--	.431	.203	5.50
75 THRU 100	.75	--	.431	.234	5.50

EC #	DATE	CHG BY	RESP ENG	CHANCE TOLERANCE CHART .X ± .060 FRAC ± 1/16 ANGLES ± 2° .XX ± .030 ADD DRAFT (UNLESS NOTED) .XXX ± .005 CASTING ± FORGINGS 7	HUBBELL POWER SYSTEMS POWER SYSTEMS, INC.
DESC OF DWG			AREAS AFFECTED BY LATEST EC Y N S.P.C. - X F.A.I. - X TOOL/EQUIP - X SUPPLIER - X GAUGES - X PRCS PROC - X PKG/LABEL - X INSP/TEST - X		
REASON (S) FOR CHANGE: - DISPOSITION OF MATL: -				SIZE C DWG NO. PSSAQHFUSELINK CAT / PART / ASSY NO. SEE CHART REV -	DO NOT SCALE THIS DRAWING DRN BY HENARD DATE 08/03/15 SHEET 1 OF 1