	6	5	4	3	2	1	
		er alloy, type 110 etp, astm b187 Ncroinches required		ZONE REV.	REVISIONS	DRAWN BY DATE A	APPR.
F	2 MINIMUM SURFACE FINISH 125 M ON ALL SURFACES UNLESS OTHE	RWISE NOTED					F
E	3,79[96,3]						
	(		· · · · ·				
D							D
	∠ φ,75	[19,1]	Φ,25	57 [6,5] —∕ <b>3/4-12 UN</b> ∙	.50[1	2,7]	-
С							С
В							В
A	This drawing is the proprietary property domain, and is issued with the express reproduced or copied in whole or in po directly or indirectly, in any way detrim and is to be returned upon request by 1	of Electro Composites (2008) ULC, not po understanding and agreement that it is n art or issued for furnishing information to o ental to the interest of Electro Composite Electro Composites (2008) ULC. All Rights	art of the public to to be others, or used s (2008) ULC Reserved.	REMOVE BURRS AND BREAK SHARP EDGES DIMENSIONS ARE IN	AANN BY: A.SAVARD DATE: BCCE BY: OECT NG : DATE: A.SAVARD CODE TOBMAT CAGE CODE A.SAVARD CAGE CODE A.SAVARD CAGE CODE		NR
	6	5	4	3	2	1	