


BOLT:
056122P
LOCKWASHER:
055054P
NUT:
056630P

Mechanical Ratings:
 Max. Total Load: 300 lb.
 Rated working load (per wire holder):

- Vertical: 150 lb.
- Side Load: 100 lb.

Electrical Ratings
 GLOSSY, CLEAN AND DRY EPOXIGLAS®
 15kV Phase to Phase
 34kV Phase to Phase with M48057
 Insulators are used on each wireholder



M480515



M480517

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.				HUBBELL POWER SYSTEMS	
		TITLE EXTENSION ARM, UNIVERSAL			
SIZE	DWG NO.	CAT / PART / ASSY NO.		REV	
B	SA4004101	PSC4004101		A	
DO NOT SCALE THIS DRAWING	DRN BY TLK	DATE 1/2/20	SHEET 1/1		