



| CAT. NO. | USA PART NO. | "A" | "B" | "C" |
|-------------|--------------|-----|------|------|
| 881P | 881PUSA | 5 | 5.75 | 3 |
| 881AP | 881APUSA | 5 | 6.50 | 3 |
| 883P | 883PUSA | 6 | 6.50 | 3 |
| 884P | | 6 | 5.75 | 3 |
| T2060610P | | 6 | 7.50 | 3 |
| PSC2061102P | | 6 | 2.50 | 2.25 |
| PS8835TP | | 6 | 6.50 | 5 |

-NOTE-

1. MATERIAL: STEEL, HOT DIP GALVANIZED PER ASTM A153 (LATEST REVISION) EXCEPT CONDUCTIVE NYLON THREAD.
2. CATALOG NUMBERS WITH A "USA" SUFFIX HAVE ALL COMPONENTS MELTED/MANUFACTURED IN THE USA.

| | | | | |
|---|-----------------------------|---|--------------------------|-----------------|
| | HUBBELL POWER SYSTEMS, INC. | | | |
| | NYLON THREAD FORGED LV PIN | | | |
| CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION, OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS, HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS. | SIZE B | CAT / PART / ASSY NO. SEE CHART | DWG NO. SA881P | REV B |
| DO NOT SCALE THIS DRAWING | DRN BY RN | DATE 5/8/2023 | SHEET 1 OF 1 | |