







CAT.#	"A"	SCREW TYPE
C207-0138G	2.5	# 24-7 WOOD SCREW
C207-0139G	3.0	# 24-7 WOOD SCREW
C207-0140G	4.0	# 24-7 WOOD SCREW
C207-0141NUT	2.0	<u>5</u> BOLT
C207-014114	14.0	5/16 TOGGLE BOLT
C207-0138AL	2.5	# 24-7 WOOD SCREW
C207-0139AL	3.0	# 24-7 WOOD SCREW
C207-0139GAL	3.0	# 24-7 WOOD SCREW

--NOTES--1. MAT'L: BLACK, UV STABALIZED, GLASS REINFORCED NYLON ALLOY.

2. ZINC COATED PER ASTM A153 OR B695 CLASS 50

3.ADD G TO THE END OF CATALOG # FOR GRAY

CHANCE" TOLERANCE CHART	HUBBELL® POWER	SYSTEM
	TITLE NIVI ON MIDELIOLD	

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MAY BE MORE THE WITTEN CONSENT OF HUBBELL POWER SYSTEMS UNPUBLISH, ALL RIGHTS RESERVED HUBBELL POWER SYSTEMS UNPUBLISH ALL RIGHTS RESERVED.

SIZE | DWG NO. | CAT / PART / ASSY NO.

 C
 SAC2070138G
 SEE CHART

 DO NOT SCALE THIS DRAWING
 DRN BY JMK
 DATE 01/18/13
 SHEET 1 OF 1

1:1