



TABLE

CAT. NO.	NOMINAL POLE LENGTH	DISTANCE BETWEEN YOKE (MIN)	DISTANCE BETWEEN YOKE (MAX)	STRAIN POLE ASSEMBLIES
C4012174	6 FT (1828.8 mm)	49" (1244.6mm)	81" (2057.4 mm)	E4012151P
C4012175	7 FT (2133.6 mm)	59" (1498.6 mm)	93" (2362.2 mm)	E4012151P
C4012176	8 FT (2438.4 mm)	74" (1879.6 mm)	108" (2743.2 mm)	E4012152P
C4012177	10 FT (3048 mm)	95" (2413 mm)	129" (3276.6 mm)	E4012153P
C4012177	12 FT (3657.6 mm)	113" (2870.2 mm)	147" (3733.8 mm)	E4012154P
C4012178	14 FT (4267.2 mm)	146" (3708.4 mm)	180" (4572 mm)	E4012155P
C4012179	18 FT (5486.4 mm)	191" (4851.4")	225" (5715mm)	E4012217P

*****MAX BALANCED WORKING LOAD:**
15,000 LBS. (66.72 kN)***

CHANCE[®]



HUBBELL POWER SYSTEMS, INC.

TITLE

**HEAVY DUTY TWO POLE
STRAIN CARRIER**

SIZE
B

CAT / PART / ASSY NO.
SEE CHART

DWG NO.
SAC4012174

REV
A

DO NOT SCALE
THIS DRAWING

DRN BY GKT

DATE 10/29/2024

SHEET 1 OF 1

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION, OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.