



**-NOTES-**

1. CROSSARM: UV INHIBITED FIBERGLASS COATED WITH UV INHIBITOR PAINT, FILLED WITH FOAM AND CAPPED
2. ALUMINUM BRACKETS: 6061-T6
3. HARDWARE: GALVANIZED STEEL
4. COPPER GROUND WIRE ONLY SUPPLIED WITH CW3CA92FG.
5. STAINLESS STEEL GROUND WIRE CLIP ATTACHED WITH STAINLESS STEEL SELF TAPPING SCREW #10-16 X 1.25" (CW3CA92FG ONLY)
6. DISTANCE BETWEEN GROUND WIRE CLIPS NOT TO EXCEED 15" ON CW3CA92FG ONLY.

CATALOG NUMBER	DESCRIPTION
CW3CA92FG	3 POSITION EQUIPMENT MOUNTING BRACKET WITH GROUND
CW3CA92DNHFG	3 POSITION EQUIPMENT MOUNTING BRACKET WITHOUT GROUND

<p><b>CHANCE</b>®</p> <p><small>CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION, OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</small></p>		<p><b>HUBBELL</b>® POWER SYSTEMS, INC.</p>		<p>HUBBELL POWER SYSTEMS, INC.</p>	
		<p>TITLE <b>3 POSITION CUTOUT AND ARRESTER MOUNT, FIBERGLASS / ALUMINUM</b></p>			
SIZE <b>B</b>	CAT / PART / ASSY NO. <b>SEE CHART</b>	DWG NO. <b>SACW3CA92FG</b>	REV <b>C</b>	<p>DO NOT SCALE THIS DRAWING</p>	
DRN BY HOEK		DATE 9/4/19	SHEET 1 OF 1		