


ASSY NO.	DESCRIPTION	'A'
PSDA101200	1" DOUBLE ARM BOLT	12"
PSDA101400	1" DOUBLE ARM BOLT	14"
PSDA101600	1" DOUBLE ARM BOLT	16"
PSDA101800	1" DOUBLE ARM BOLT	18"
PSDA102000	1" DOUBLE ARM BOLT	20"
PSDA102200	1" DOUBLE ARM BOLT	22"
PSDA102400	1" DOUBLE ARM BOLT	24"
PSDA102600	1" DOUBLE ARM BOLT	26"
PSDA102800	1" DOUBLE ARM BOLT	28"
PSDA103000	1" DOUBLE ARM BOLT	30"
PSDA103200	1" DOUBLE ARM BOLT	32"
PSDA103400	1" DOUBLE ARM BOLT	34"
PSDA103600	1" DOUBLE ARM BOLT	36"
PSDA103800	1" DOUBLE ARM BOLT	38"
PSDA104000	1" DOUBLE ARM BOLT	40"
PSDA104200	1" DOUBLE ARM BOLT	42"

-NOTES-

1. HOT DIP GALVANIZE PER ASTM A153 (LATEST REVISION).
2. ALL BOLTS AND NUTS MEET REQUIREMENTS OF ANSI C135.1.
3. TENSILE STRENGTH OF 33,500 LB. MIN.

CHANCE TOLERANCE CHART		 HUBBELL POWER SYSTEMS <small>POWER SYSTEMS, INC.</small>		
<small>CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</small>		TITLE 1" DOUBLE ARM BOLT		
		SIZE SB SADA101200	DWG NO. SEE CHART	CAT / PART / ASSY NO. SEE CHART
<small>DO NOT SCALE THIS DRAWING</small>		DRN BY JJL	DATE 03/05/09	SHEET 01 OF 01