



1/2-13UNC-2A X 2" CARRIAGE BOLT WITH  
HEX NUT, LOCKWASHER, AND  
INTERNAL-EXTERNAL TOOTH LOCKWASHER

**NOTES**

1. HOT DIP GALVANIZED PER ASTM A153
2. HOLE PATTERN SAME FOR BACKSTRAP EXCEPT ROUND HOLE IS OMITTED
3. USE 3/8-16UNC-2A X 5 1/2" CARRIAGE BOLTS
4. USE 3/8-16UNC-2A X 6" CARRIAGE BOLTS

CATALOG NUMBER	"A"	"B"	NOTES
DM36B4	9 1/16	2 3/4 TO 4 1/2	NOTE-3
DM55B2	9 1/8	2 3/4 TO 4 1/2	NOTE-3
PSC2061053	9 1/8	3 1/4 TO 5	NOTE-4

**CHANCE**®



HUBBELL POWER SYSTEMS, INC.

TITLE

**BRACKET  
CUTOUT AND ARRESTER**

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION, OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.

SIZE <b>C</b>	CAT / PART / ASSY NO. <b>SEE CHART</b>	DWG NO. <b>SADM36B4</b>	REV <b>A</b>
DO NOT SCALE THIS DRAWING	DRN BY WITTEN	DATE 01/22/13	SHEET 1 OF 1