



3/8-16-UNC HEX NUT AND BOLT  
W/ 3/8 SPRING LOCK WASHER

-NOTES-

1. MATERIAL: MOUNTING BRACKET: STEEL PER TT-169  
BACK STRAP: ALUMINUM ALLOY 5052-H32  
INSULATOR: COMMERCIAL GRADE DRY PROCESS PORCELAIN.
2. FINISH: MOUNTING BRACKET: HOT DIP GALVANIZE PER  
ASTM A153(LATEST REVISION)  
INSULATOR: WHIT GLAZE.

CATALOG NUMBER	"A"	"B"	"C"	"D"	"E"	"F"
DU27M1	.88	1.13	3.18	2.50	2.50	4.19
DU27M2	1.25	1.5	3.88	3.13	2.94	4.88
DU27M3	1.75	2	4.50	3.81	3.75	5.50
DU27M4	2.25	2.5	5.12	4.44	3.75	6.13
DU27M5	2.75	3	5.76	5.13	4.00	6.75

LATEST EC NO:		REV.	DATE	CHANGED BY	RESP ENGINEER
46940		-	-	----	----
				DO NOT SCALE THIS DWG	THIRD ANGLE PROJECTION
				ISO DUAL DIMENSIONS IN=INCH, MM=MILLIMETER	
DRN BY:	DATE	TITLE:			SIZE
BERGER	08-10-12	INSULATED CABLE SUPPORT			B



CHANCE®



DWG NO:  
SADU27M1

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS, INC. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT WRITTEN CONSENT BY HUBBELL POWER SYSTEMS, INC. © 2012 HUBBELL POWER SYSTEMS. UNPUBLISHED, ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS